

IPP-82A0030MIA

SKU: 212715



1/2,8" Network Dome, 1920x1080, PTZ, Day&Night, 4,3-129mm, Infrared, IP66

Main Features

1/2.8" Sony CMOS-Sensor

30x AF Zoom, 4,3~129mm / Digital zoom

Full HD 1920x1080 pixels, 1080p@50/60fps

Compression H.264/MJPEG, Web Casting

Digital noise reduction (DNR)

VCA Video Analytic

Zoom synchronized & fixed IR LEDs

Real time WDR (Wide Dynamic Range) 25/30fps

DIS (Digital Image Stabilization)

Privacy zones

Alarm in- and outputs, micro SD card slot

High-PoE midspan included

Specifications

Dimensions (HxWxD)	315x201.38mm
Series	eneo SN-Series
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	60 fps
Day&Night switch	ICR

IPP-82A0030MIA

Continuation of the specifications

Sensitivity	0,35 Lux at F1,6, 50 IRE
Digital Noise Reduction	yes
Lens Type	auto focus zoom
Focal Length	4,3 - 129,0 mm
Iris Control	DC
Zoom Factor	30x
Digital Zoom	16x
Horizontal Angle of View	61,8 - 2,11°
Vertical Angle of View	36,4 - 1,29°
MOD (Minimum Object Distance)	1 m
Illumination	Infrared
Housing	Outdoor
Color (housing)	Pantone Cool Gray 1C
Housing material	Aluminium, Plastic
Heater	no
Rotation range	360°
Speed (manual)	380°/Sek.
Alarm inputs	4
Alarm outputs	1
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	Defog, Field detection, Gesichtserkennung, Motion detection, Tampering protection, Trip wire plus object counting
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	28W
Power over Ethernet	IEEE 802.3at
Vandal proof	no
Operating temperature	-30°C ~ 65°C
ONVIF	ONVIF Profile S
Protection rating	IP66
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Camera type	PTZ
Audio	2 Way Audio
Remote configuration	Browser
Illumination range	approx. 300m

IPP-82A0030MIA

Continuation of the specifications

Weight	4.9kg
Manufacturer order number	212715

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

