



IPD-72A0003M0A

SKU: 213013



1/3" Network Dome, Fixed, 1920x1080, Day&Night, AF Zoom, WDR, 3-9mm, Infrared, IP67

Main Features

1/3" Panasonic CMOS Sensor

Resolution max. 1920x1080 (Full HD)

Optical 3x Auto Focus Zoom, 16x Digital

3~9 mm day&night zoom lens, IR cut filter

Cross Web Browsing (IE, Safari, Firefox, Chrome)

Responsive Web Design, Zero configuration

Triple Streaming: 2x H.264, 1x MJPEG

VerticalView 90°/270° mode only H.264, HTML5 Playback

Real time WDR (Wide Dynamic Range) 25/30fps

Slot for Micro SD card

ONVIF conformity, PoE IEEE802.af

Hard Coated Bubble, scratch resistant

Specifications

Dimensions (HxWxD)	119x140mm
Series	eneo KN-Series
Resolution Standard	HD 1080p, HD 720p
System	True Day&Night
Sensor size	1/3"
Imager	CMOS
Video compression	H.264, M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps
Day&Night switch	ICR

IPD-72A0003M0A

Continuation of the specifications

Sensitivity	0,35 Lux at F1,2, 40 IRE
Digital Noise Reduction	yes
Lens Type	auto focus zoom
Focal Length	3 - 9 mm
Iris Control	DC
Zoom Factor	3x
Digital Zoom	16x
Horizontal Angle of View	90 - 32°
Vertical Angle of View	50 - 18°
MOD (Minimum Object Distance)	0,5 m
Illumination	Infrared
Housing	Outdoor
Color (housing)	Pantone Cool Gray 1C
Color (bubble)	clear
Housing material	Aluminium
Heater	yes
Blower	yes
Video outputs	no
Alarm inputs	1
Alarm outputs	1
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	Cross Counting (CC), Defog, Motion detection, Perimeter Intrusion Detection (PID), Tampering Detection (TD)
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, 24VAC, PoE
Power consumption	9W
Power over Ethernet	IEEE 802.3af
Vandal proof	yes
Operating temperature	-50°C ~ +50°C
ONVIF	ONVIF Profile S
Certifications	IK10
Protection rating	IP67
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	WDR 113dB
Motion Detector	yes
Camera type	Dome
Audio	2 Way Audio

IPD-72A0003M0A

Continuation of the specifications

Remote configuration	Browser
Illumination range	approx. 40m
Weight	1 kg
Manufacturer order number	213013

Optional Accessory

SKU	Name	Description
209832	AK-5	Camera Junction Box, for Callisto Dome series, IP66
216923	DOMES-S1	Sun Shield for eneo Callisto Dome Series
209880	DOMES-WB1+DOMES/ Basis1	Wall Bracket & Surface mount base, Callisto Dome line
209831	DOMES/BASIS1	Surface mount base , Callisto Dome line
207192	DOMES/WEDGE2	Wedge Adapter, Callisto Dome Line
218218	eneo Site Manager	Management Software for eneo IP products

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

