



IPC-55C0000M0A

SKU: 213022



1/1.8" Network Camera, 2592x1944, Day&Night, D-WDR, C/CS, Indoor

Main Features

1/1.8" 5.0 Megapixel RGB Bayer Array CMOS

Resolution max. 2592x1944

C/CS lens mount, IR cut filter

Cross Web Browsing (IE, Safari, Firefox, Chrome)

Responsive Web Design, Zero configuration

Triple Streaming: 2x H.264, 1x MJPEG

VerticalView 90°/270° mode only H.264, HTML5 Playback

Digital Wide Dynamic Range (D-WDR)

LDC (Lens Distortion Correction), Defog function

Slot for Micro SD card

ONVIF conformity, PoE IEEE802.af

External input for day&night switching

Specifications

Manufacturer order number	213022
---------------------------	--------

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
213619	H04Z03NFDC-MP	F1,5/4-13mm, Megapixel DC-Lens, variable Focal Length, 1/1.8" CS-Mount
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop

IPC-55C0000M0A

Continuation of accessory

218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug
219504	WD-30	Wall Mount Bracket with Ball Joint, 1/4" Camera Fixing Screw, Pantone Cool Grey 1C

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

