

IPP-72A0030M0A

SKU: 213541



1/2.8" Network Dome, PTZ, 30x AF Zoom, Day&Night, 1920x1080, PoE, IP66, 12/24V

Main Features

1/2.8" Sony CMOS-Sensor

30x AF Zoom, 4.3~129mm / 16x Digital

Full HD 1920x1080 pixels, 1080p@50/60fps

Compression H.264/MJPEG, Web Casting

Digital Noise Reduction (DNR)

VCA Video Analytic

Real time WDR (Wide Dynamic Range) 25/30fps

Digital Image Stabilization (DIS)

Privacy zones

Alarm in- and outputs

ONVIF conformity

Specifications

Dimensions (HxWxD)	278x234mm
Series	eneo SN-Series
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	60 fps
Day&Night switch	ICR

IPP-72A0030M0A

Continuation of the specifications

Sensitivity	0,35 Lux at F1,6, 50 IRE
Digital Noise Reduction	yes
Lens Type	auto focus zoom
Focal Length	4,3 - 129,0 mm
Iris Control	DC
Zoom Factor	30x
Digital Zoom	16x
Observe (62 px/m)	25 - 840 m
Recognize (125 px/m)	12 - 400 m
Identify (250 px/m)	6 - 200 m
Detect (25px/m)	64 - 2000 m
Horizontal Angle of View	61,8 - 2,11°
Vertical Angle of View	36,4 - 1,29°
MOD (Minimum Object Distance)	1 m
Illumination	no
Housing	Outdoor
Color (housing)	Pantone Cool Gray 1C
Color (bubble)	clear
Housing material	Aluminium
Heater	yes
Blower	yes
Rotation range	360°
Speed (manual)	380°/Sek.
Alarm inputs	4
Alarm outputs	1
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	Defog, Field detection, Gesichtserkennung, Motion detection, Tampering protection, Trip wire plus object counting
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, 24VAC, PoE
Power consumption	(with heater), 13W, 50W, w./o. heater
Power over Ethernet	IEEE 802.3af
Vandal proof	yes
Operating temperature	-50°C ~ +65°C
ONVIF	ONVIF Profile S
Certifications	IK10
Protection rating	IP66
Low Speed Shutter	yes

IPP-72A0030M0A

Continuation of the specifications

Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Camera type	PTZ
Audio	2 Way Audio
Remote configuration	Browser
Weight	3.3kg
Manufacturer order number	213541

Optional Accessory

SKU	Name	Description
74125	EDC-AKS1	Power&Connection Box with Mounting Bracket for In/Outdoor, 230V-24VAC/3.0A
220314	EDC-WMB1-W	Wall Mount for PTZ Dome Cameras, white, with Mounting Kit
218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

