



# IAR-7SE1024MMA

SKU: 214460



Gigabit Switch, 2x RJ45, 24x PoE 100Mbps, 2xSFP 1000Mbps, 390W, Managed, 19", 1U

## Main Features

PoE Switch, Rack Montage

Gigabit Uplink Ports: 2xRJ45, 2xSFP

24x 10/100 PoE Ports, IEEE 802.3af/at

Up to 30W per port, Total ≤390W

ESD protection IEC61000-4-5 standard

Managed L2 switch, Built in low-noise fans

Web configuration, Web management

VLAN, PoE management, MAC address table

Port mirroring, password

Status LEDs

Temperature range -10°C ~ + 50°C

Rack mounting brackets included

## Specifications

Dimensions (HxWxD)	44,5x442x263mm
Type	Layer2 switch
Series	eneo Switch
Mounting	19" rack, desktop
Blower	yes
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
VLAN	yes
Ports	24x 10/100Base-TX, 2x 10/100/1000Base-TX, 2x 10/100/1000T SFP, Console RJ45-RS232
PoE ports (number)	24
Management	yes

# IAR-7SE1024MMA

Continuation of the specifications

Model	Desktop, Rack Mount
Supply voltage	100~240VAC
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
PoE budget	390 W
Operating temperature	-10°C ~ +50°C
Weight	3.8kg
Manufacturer order number	214460

## Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

