



IED-63M2812P0A

SKU: 214560



1/2.8" Network Dome, Fixed, Day&Night, 2048x1536, Infrared 2.8-12 mm, 12VDC, PoE, Indoor

Main Features

1/2.8" Sony STARVIS CMOS-Sensor

Megapixel varifocal lens, motorized,

2.8~12mm, True Day & Night

Resolution max. 2048x1536

Compression H.264/MJPEG, Web Casting

Cross Web-Browsing, ONVIF

VerticalView 90°/270° Mode, H.264 only

VCA Video Analytic

D-WDR (Digital Wide Dynamic Range)

Framerate increase on motion detection

OpenVPN Support

Indoor application

Specifications

Observe (62 px/m)	18 - 52 m
Recognize (125 px/m)	9 - 24 m
Identify (250 px/m)	5 - 13 m
Detect (25px/m)	45 - 129 m
Manufacturer order number	214560

Optional Accessory

SKU	Name	Description
225730	AK-9B	Camera junction box for DH-6, Dome-WB4

IED-63M2812P0A

Continuation of accessory

218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop

Optional Services

SKU	Name	Description
211125	LACKIERUNG Fix-Dome-Kamera	Extra charge for special paint fixed dome in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

