

# IAD-5SG1008MUA

SKU: 216472



Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop

## Main Features

Gigabit PoE Switch, desktop application

Gigabit Uplink Ports: 1x RJ45, 1x SFP

8x 10/100/1000 PoE Ports, IEEE 802.3af/at

Up to 30W per Port, Total  $\leq 120W$

ESD protection IEC61000-4-2 Standard

CCTV mode allows transmission up to 250m @ 10Mbps

Brackets and 150W power-adaptor scope of supply

## Specifications

Dimensions (HxWxD)	27x200x101,8mm
Type	Layer2 switch
Series	eneo Switch
Mounting	desktop
Blower	no
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
VLAN	no
Ports	1x 10/100/1000Base-Tx, 1x 1000Base-X SFP, 8x 10/100/1000Base-T
PoE ports (number)	8
Management	no
Model	Desktop
Supply voltage	48~57 VDC

# IAD-5SG1008MUA

Continuation of the specifications

Power over Ethernet	IEEE 802.3af, IEEE 802.3at
PoE budget	120 W
Operating temperature	-10°C ~ +45°C
Weight	500g
Manufacturer order number	216472

## Optional Accessory

SKU	Name	Description
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

