



IPD-73M2812MWA

SKU: 216602



1/2.8" Network Dome, Fixed, 2048x1536, Day&Night, D-WDR, 2.8-12mm, Infrared, IP67

Similar as above image

Main Features

1/2.8" Sony STARVIS CMOS

Initial configuration via optional Wi-Fi dongle

Motorized varifocal lens, 2.8~12 mm

Push Focus for easy lens adjustment

Cross Web Browsing (IE, Safari, Firefox, Chrome)

Responsive Web Design, Zero configuration

Triple Streaming: 2x H.264, 1x MJPEG

VerticalView 90°/270° mode (H.264 only), HTML5 Playback

Digital Wide Dynamic Range (D-WDR)

LDC (Lens Distortion Correction), Defog function

ONVIF conformity, PoE IEEE802.af

3-Axis gimbal, IP67

Specifications

Manufacturer order number	216602
---------------------------	--------

Optional Accessory

SKU	Name	Description
209832	AK-5	Camera Junction Box, for Callisto Dome series, IP66
216923	DOME-S1	Sun Shield for eneo Callisto Dome Series
209880	DOME-WB1+DOME/ Basis1	Wall Bracket & Surface mount base, Callisto Dome line
209831	DOME/BASIS1	Surface mount base , Callisto Dome line

IPD-73M2812MWA

Continuation of accessory

207192	DOME/WEDGE2	Wedge Adapter, Callisto Dome Line
218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

