



MPC-52C0000M0A

SKU: 217280



1/2.8" HD Camera, Day&Night, 1920x1080, WDR, C/CS, 12/24V

Abb. ähnlich|The lens ist not part of the delivery

Main Features

- 1/2.8" 2 Megapixel SONY STARVIS CMOS sensor
- Resolution max. 1920x1080 pixels (Full HD)
- Separate outputs for digital and multi-signal
- Multisignal: HD-TVI, AHD, CVI and Composite selectable
- Digital signal: EX-SDI, HD-SDI selectable

- Removable infrared cut filter
- ROI (Region of Interest) WDR mode
- Integrated motion detector, defog, privacy zones
- C/CS mount, LSC (Lens shading compensation)

Specifications

Dimensions (HxWxD)	72x74x89mm
Serial interfaces protocols	UTC (HD-Signal Format)
Series	eneo COAXIZE, eneo KX-Series
Resolution Pixels	1280x720, 1920x1080, 720x576
Resolution Pixels	1280x720, 1920x1080, 720x576
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Day&Night switch	ICR
Sensitivity	0,08 Lux at F1,4, 40 IRE
Digital Noise Reduction	yes
Iris Control	DC

MPC-52C0000M0A

Continuation of the specifications

Housing	Indoor
Color (housing)	Pantone Cool Gray 1C
Housing material	Aluminium
Video outputs	AHD, Composite (CVBS), CVI, EX-SDI, HD-SDI, HD-TVI
Alarm inputs	nein
Alarm outputs	no
Serial interfaces	Coaxitron (HD Protocol)
Analysis functions	Defog
Supply voltage	12VDC, 24VAC
Power consumption	5W
Operating temperature	-10°C ~ +50°C
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	WDR 113dB
Motion Detector	yes
Signal format	AHD @ 2MP, Composite (FBAS), CVI @ 2MP, EX-SDI (270 Mbps), HD-SDI (1.485 Gbps), HD-TVI @ 2MP
Camera type	Box
Frame rate	25/30fps @ 1920x1080p, 50/60fps @ 1280x720p
Weight	290g
Manufacturer order number	217280

Optional Accessory

SKU	Name	Description
213619	H04Z03NFDC-MP	F1,5/4-13mm, Megapixel DC-Lens, variable Focal Length, 1/1.8" CS-Mount
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
236125	MAM-5MM2203M0A	Converter, 4K HD-TVI, HD-CVI, AHD, auf HDMI, Indoor 12VDC
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive
219504	WD-30	Wall Mount Bracket with Ball Joint, 1/4" Camera Fixing Screw, Pantone Cool Grey 1C

MPC-52C0000M0A

Continuation of accessory

Optional Services

SKU	Name	Description
211123	LACKIERUNG Bulletkamera	Extra charge for special paint bullet camera in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229233	Vorkonfiguration analoge Kamera	Preconfiguration 1x analog camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

