

MPD-64A0003P0A

SKU: 218771



1/2,9" HD Dome, Fixed 2560x1440, Day&Night, AF Zoom, WDR, 3,2-9mm, Infrared, Indoor

Main Features

1/2,9" 6,64 Megapixel SONY STARVIS CMOS-Sensor
Resolution max. 2560x1440@25/30fps
Optical 3x auto focus zoom, 3,2~9mm
Separate outputs for digital and multi-signal
Multisignal: HD-TVI, AHD selectable, Composite SUB
Digital signal: EX-SDI, HD-SDI selectable

DOL-WDR by triple scan images at 30/25fps & ROI (Region of Interest) WDR mode
Point of Interest & Smart Motion Zoom
Wedge adapter included (10° inclination)
Scratch resistant hard coated bubble
Easy installation, 3-Axis gimbal

Specifications

Dimensions (HxWxD)	94x116mm
Serial interfaces protocols	UTC (HD-Signal Format)
Series	eneo Callisto Indoor, eneo COAXIZE, eneo KX-Series
Resolution Pixels	1280x720, 1920x1080, 2560x1440
Resolution Pixels	1280x720, 1920x1080, 2560x1440
System	True Day&Night
Sensor size	1/2.9"
Imager	CMOS
Day&Night switch	ICR
Sensitivity	0,1 Lux at F1,6, 40 IRE

MPD-64A0003P0A

Continuation of the specifications

Digital Noise Reduction	yes
Lens Type	auto focus zoom
Focal Length	3,2 - 9 mm
Iris Control	DC
Zoom Factor	3x
Digital Zoom	yes
Observe (62 px/m)	32 - 88 m
Recognize (125 px/m)	14 - 43 m
Identify (250 px/m)	6,6 - 21 m
Detect (25px/m)	80 - 215 m
Horizontal Angle of View	75 - 26°
Vertical Angle of View	41 - 15°
MOD (Minimum Object Distance)	0,5 m
Illumination	Infrared
Housing	Indoor
Color (housing)	white
Color (bubble)	clear
Housing material	Plastic
Heater	no
Blower	no
Rotation range	+/-165°
Video outputs	AHD, composite (CVBS) SUB, EX-SDI, HD-SDI, HD-TVI
Alarm inputs	nein
Alarm outputs	no
Serial interfaces	Coaxitron (HD Protocol)
Analysis functions	Defog, Digital image stabilization
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC
Power consumption	7W
Vandal proof	no
Operating temperature	-10°C ~ +50°C
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR, WDR 113dB
Motion Detector	yes
Signal format	AHD @ 4MP, EX-SDI @ 4MP, HD-SDI (1.485 Gbps), HD-TVI @ 4MP
Camera type	Dome
Frame rate	25/30fps @ 1920x1080p, 25/30fps @ 2560x1440p, 50/60fps @ 1280x720p
Aperture range (F)	F1.6

MPD-64A0003P0A

Continuation of the specifications

Illumination range	approx. 30m
Weight	260g
Manufacturer order number	218771

Optional Accessory

SKU	Name	Description
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
236125	MAM-5MM2203M0A	Converter, 4K HD-TVI, HD-CVI, AHD, auf HDMI, Indoor 12VDC
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive

Optional Services

SKU	Name	Description
211125	LACKIERUNG Fix-Dome-Kamera	Extra charge for special paint fixed dome in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229233	Vorkonfiguration analoge Kamera	Preconfiguration 1x analog camera Function test, FW update

MPD-64A0003P0A

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

