



ITB-7SF0013M0A

SKU: 219421



Thermal Network Camera, 13mm, 25°, 336x256, 25Hz, Audio, Composite, PoE, IP67

Main Features

Thermal camera with Ethernet and Composite Video out

Resolution 336x256 Pixel, 25 Hz

13mm lens, 25° viewing angle

Easy handling, USB remote interface

Alarm output contact triggers by temperature measurement

Simultaneously H.264 & MJPEG (Triple streaming)

Cross Web Browsing (IE, Safari, Firefox, Chrome)

VerticalView 90°/270°, Audio

Responsive Web Design, Zero Configuration

HTML5 playback, Slot for micro SD memory card

Easy installation, fixation via central screw

Flexible power supply 12VDC, 24VAC or PoE

Specifications

Manufacturer order number	219421
---------------------------	--------

Optional Accessory

SKU	Name	Description
202888	AK-4	Camera junction box, for Candid Small ,Candid Medium, Series
218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop

ITB-7SF0013M0A

Continuation of accessory

202641	PM-42A	Pole mount adaptor for eneo Candid, Candid S, Candid M, WB1, AK-5, AK-4
214174	VerticalView Adaptor	For IP Candid Medium Series using the VerticalView mode Mode

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

