



IAM-5SG1004MMA

SKU: 219526



Gigabit Switch, Managed, 120W, 4x PoE, 2x SFP, 1000Mbps, Industrial Design, -40°C~+75°C

Main Features

Gigabit PoE Switch, DIN Rail

2x SFP Gigabit Uplink Ports

4x 10/100/1000 PoE Ports, IEEE 802.3af/at

Supports VLAN, RTSP, "Fast Ring", and QoS

Up to 30W per port, Total ≤120W

Fast Ring-Redundant, Reconfiguration <20ms

Supports redundant power supply connection

ESD protection IEC61000-4-5 Standard

Web configuration, Web management

Fault Relay, Console Port, Status LED

PoE reset button for each port

CCTV mode allows transmission up to 250m @ 10Mbps

Specifications

Dimensions (HxWxD)	46,5x110x163mm
Type	Layer2 switch
Series	eneo Switch
Mounting	DIN rail, wall mount
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
VLAN	yes
Ports	2x 1000Base-X SFP, 4x 10/100/1000Base-T
PoE ports (number)	4
Management	yes
Model	DIN rail module

IAM-5SG1004MMA

Continuation of the specifications

Supply voltage	48~57 VDC
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
PoE budget	120 W
Operating temperature	-40°C ~ +75°C
Weight	680g
Manufacturer order number	219526

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

