



# MED-62V2812M0B

SKU: 219547



1/2,8" HD Dome, Fix, Day&Night, 1920x1080, 12VDC, 2,8-12mm, Infrared, IP66

## Main Features

- 1/2.8" 2.3 Megapixel progressive scan CMOS sensor
- Compact metal housing for outdoor use
- Resolution max. 1920x1080 (Full HD)
- Multisignal: HD-TVI, AHD, CVI, Composite selectable
- Variofocal 2.8~12mm day&night lens
- LSC (Lens shading compensation)

- Removable infrared cut filter
- RS-485 control in-output
- 3D-DNR noise reduction
- Integral motion detection
- Scratch resistant hard coated bubble
- Easy installation, 3-Axis gimbal

## Specifications

Serial interfaces protocols	UTC (HD-Signal Format)
Observe (62 px/m)	19 - 57 m
Recognize (125 px/m)	9 - 28 m
Identify (250 px/m)	4 - 14 m
Detect (25px/m)	48 - 135 m
Manufacturer order number	219547

## Optional Accessory

SKU	Name	Description
-----	------	-------------

# MED-62V2812M0B

## Continuation of accessory

230864	AK-11	Camera junction box for wall and ceiling mounting
215644	DOME-WB3	Wall bracket for eneo Dome Cameras MED-62xxxxM0A and IED-62xxxxM0A
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive

## Optional Services

SKU	Name	Description
211125	LACKIERUNG Fix-Dome-Kamera	Extra charge for special paint fixed dome in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229233	Vorkonfiguration analoge Kamera	Preconfiguration 1x analog camera Function test, FW update

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

