



IEB-74M2812MAA

SKU: 219588



1/3" Network Camera, 2592x1520, Day&Night, WDR, 2,7-12mm, Infrared, IP66

Main Features

1/3" OmniVision CMOS	Micro SD Card (SDHC, SDXC)
Resolution max. 2592x1520, 25fps frame rate	1 x Alarm in and output as well as audio support
Motorised vary focal lens 2,7~12mm with P-Iris	Infrared illumination up to 30m
Intelligent self learning video analysis (IntelliVision inside)	Easy installation, IP66
Wide Dynamic Range, T-WDR (120dB)	PoE IEEE 802.3af Class 0, 12VDC
Quad Streaming: H.264, H.265 x3, MJPEG x1, Smart Codec Support	Supports ONVIF Profile S und Profile T

Specifications

Dimensions (HxWxD)	86x90x279mm
Series	eneo SN-Series
Resolution Standard	4 Megapixel
System	True Day&Night
Sensor size	1/3"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	2592x1520
Image Transmission Rate	30 fps
Day&Night switch	ICR

IEB-74M2812MAA

Continuation of the specifications

Sensitivity	0,14 Lux at F1,6, 40 IRE
Digital Noise Reduction	yes
Lens Type	Varifocal (motorized)
Focal Length	2,7 - 12 mm
Iris Control	DC, P-iris
Zoom Factor	4x
Digital Zoom	yes
Observe (62 px/m)	22 - 75 m
Recognize (125 px/m)	11 - 36 m
Identify (250 px/m)	6 - 18 m
Detect (25px/m)	58 - 180 m
Horizontal Angle of View	97 - 31°
Vertical Angle of View	55 - 18°
MOD (Minimum Object Distance)	0,5 m
Illumination	Infrared
Housing	Outdoor
Color (housing)	white
Housing material	Aluminium
Blower	no
Video outputs	no
Alarm inputs	1
Alarm outputs	1
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	Cross Counting (CC), Human (PD), Loitering detection, Motion detection, Perimeter Intrusion Detection (PID), Tampering Detection (TD)
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	9W
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-20°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Protection rating	IP66
Low Speed Shutter	yes
Backlight Compensation	BLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Camera type	Bullet

IEB-74M2812MAA

Continuation of the specifications

Audio	2 Way Audio
Remote configuration	Browser
Illumination range	approx. 30m
Weight	860g
Manufacturer order number	219588

Optional Accessory

SKU	Name	Description
225730	AK-9B	Camera junction box for DH-6, Dome-WB4
218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop

Optional Services

SKU	Name	Description
211123	LACKIERUNG Bulletkamera	Extra charge for special paint bullet camera in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

