



IED-64M2812MAA

SKU: 219808



1/3" Network Dome, Fixed, 2592x1520, Day&Night, WDR, 2,7-12mm, Infrared, IP66

Main Features

1/3" OmniVision CMOS	Micro SD Card (SDHC, SDXC)
Resolution max. 2592x1520, 25fps frame rate	1 x Alarm in and output as well as audio support
Motorised varifocal lens 2,7~12mm with P-Iris	Infrared illumination up to 30m
Intelligent self learning video analysis (IntelliVision inside)	Easy installation, IP66
Wide Dynamic Range, T-WDR (120dB)	PoE IEEE 802.3af Class 0, 12VDC
Quad Streaming: H.264, H.265 x3, MJPEG x1, Smart Codec Support	Supports ONVIF Profile S und Profile T

Specifications

Observe (62 px/m)	22 - 75 m
Recognize (125 px/m)	11 - 36 m
Identify (250 px/m)	6 - 18 m
Detect (25px/m)	58 - 180 m
Manufacturer order number	219808

Optional Accessory

SKU	Name	Description
225730	AK-9B	Camera junction box for DH-6, Dome-WB4

IED-64M2812MAA

Continuation of accessory

218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop
223980	IED-FMH1	Ceiling mount adapter with white cover for fix dome cameras, SN-series

Optional Services

SKU	Name	Description
211125	LACKIERUNG Fix-Dome-Kamera	Extra charge for special paint fixed dome in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

