



# IEB-72M2812MAA

SKU: 220082



1/2.8" Network Camera, 1920x1080, Day&Night, WDR, 2,8-12mm, Infrared, IP66

## Main Features

1/2,8" Sony STARVIS CMOS	Micro SD Card (SDHC, SDXC)
Resolution max. 1920x1080, 25fps frame rate	1 x Alarm in and output as well as audio support
Motorised vary focal lens 2,8~12mm with P-Iris	Infrared illumination up to 30m
Intelligent self learning video analysis (IntelliVision inside)	Easy installation, IP66
Wide Dynamic Range, T-WDR (120dB)	PoE IEEE 802.3af Class 0, 12VDC
Quad Streaming: H.264, H.265 x3, MJPEG x1, Smart Codec Support	Supports ONVIF Profile S und Profile T

## Specifications

Observe (62 px/m)	16 - 55 m
Recognize (125 px/m)	8 - 26 m
Identify (250 px/m)	4 - 13 m
Detect (25px/m)	40 - 130 m
Manufacturer order number	220082

## Optional Accessory

SKU	Name	Description
225730	AK-9B	Camera junction box for DH-6, Dome-WB4

# IEB-72M2812MAA

Continuation of accessory

218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop

## Optional Services

SKU	Name	Description
211123	LACKIERUNG Bulletkamera	Extra charge for special paint bullet camera in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

