



IEB-78M3611MAA

SKU: 220148



1/2.5" Network Camera, 3840x2160, Day&Night, WDR, 3,6-11mm, Infrared, IP66

Main Features

1/2,5" Sony STARVIS CMOS

4K UHD Resolution (3840x2160), 25fps frame rate

Motorised vary focal lens 3,6~11mm with P-Iris

Intelligent self learning video analysis (IntelliVision inside)

Wide Dynamic Range, True WDR (120dB)

Quad Streaming: H.264, H.265 x3, MJPEG x1, Smart Codec Support

Micro SD Card (SDHC, SDXC)

1 x Alarm in and output as well as audio support

Infrared illumination up to 30m

Easy installation, IP66

PoE IEEE 802.3af Class 0, 12VDC

Supports ONVIF Profile S and Profile T

Specifications

Observe (62 px/m)	40 - 95 m
Recognize (125 px/m)	17 - 47 m
Identify (250 px/m)	9 - 23 m
Detect (25px/m)	94 - 230 m
Manufacturer order number	220148

Optional Accessory

SKU	Name	Description
225730	AK-9B	Camera junction box for DH-6, Dome-WB4

IEB-78M3611MAA

Continuation of accessory

218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop

Optional Services

SKU	Name	Description
211123	LACKIERUNG Bulletkamera	Extra charge for special paint bullet camera in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

