



IEB-78M3611MAA

SKU: 220148



1/2.5" Network Camera, 3840x2160, Day&Night, WDR, 3,6-11mm, Infrared, IP66

Main Features

1/2,5" Sony STARVIS CMOS	Micro SD Card (SDHC, SDXC)
4K UHD Resolution (3840x2160), 25fps frame rate	1 x Alarm in and output as well as audio support
Motorised vary focal lens 3,6~11mm with P-Iris	Infrared illumination up to 30m
Intelligent self learning video analysis (IntelliVision inside)	Easy installation, IP66
Wide Dynamic Range, True WDR (120dB)	PoE IEEE 802.3af Class 0, 12VDC
Quad Streaming: H.264, H.265 x3, MJPEG x1, Smart Codec Support	Supports ONVIF Profile S and Profile T

Specifications

Observe (62 px/m)	40 - 95 m
Recognize (125 px/m)	17 - 47 m
Identify (250 px/m)	9 - 23 m
Detect (25px/m)	94 - 230 m
Manufacturer order number	220148

Optional Accessory

SKU	Name	Description
225730	AK-9B	Camera junction box for DH-6, Dome-WB4

IEB-78M3611MAA

Continuation of accessory

218218	eneo Site Manager	Management Software for eneo IP products
--------	-------------------	--

Optional Services

SKU	Name	Description
211123	LACKIERUNG Bulletkamera	Extra charge for special paint bullet camera in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

