



IED-68M3611MAA

SKU: 220149



1/2.5" Network Dome, Fixed, 3840x2160, Day&Night, WDR, 3,6-11mm, Infrared, IP66

Main Features

1/2,5" Sony STARVIS CMOS	Micro SD Card (SDHC, SDXC)
4K UHD Resolution (3840x2160), 25fps frame rate	1 x Alarm in and output as well as audio support
Motorised varifocal lens 3,6~11mm with P-Iris	Infrared illumination up to 30m
Intelligent self-learning video analysis (IntelliVision inside)	PoE IEEE 802.3af Class 0, 12VDC, IP66
Wide Dynamic Range, T-WDR (120dB)	Supports ONVIF Profile S and Profile T
Quad Streaming: H.264, H.265 x3, MJPEG x1, Smart Codec	Color Stream

Specifications

Observe (62 px/m)	40 - 95 m
Recognize (125 px/m)	17 - 47 m
Identify (250 px/m)	9 - 23 m
Detect (25px/m)	94 - 230 m
Manufacturer order number	220149

Optional Accessory

SKU	Name	Description
225730	AK-9B	Camera junction box for DH-6, Dome-WB4

IED-68M3611MAA

Continuation of accessory

218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop
223980	IED-FMH1	Ceiling mount adapter with white cover for fix dome cameras, SN-series

Optional Services

SKU	Name	Description
211125	LACKIERUNG Fix-Dome-Kamera	Extra charge for special paint fixed dome in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

