

ISD-59P0010P0A

SKU: 220196



1/1,7" Network Dome, fixed, Day/Night, 4000x3000, H.265, 1,29mm, 360°, infrared, IP66

Main Features

1/1.7" Sony STARVIS CMOS-Sensor	Quad Stream (H.264/H.265x3, MJPEGx1)
1.29mm fixed lens FishEye camera	Cross Web-Browsing
360° Panorama-, Corridor-, Quad-, Panomorph-View, ceiling TrueWDR (Digital Wide Dynamic Range)	
Integration in eneo Center Software	Framerate increase on motion detection (Smart Codec)
True Day & Night	IR-LED Illumination integrated
Resolution max. 4000x3000@20fps	Compact design for indoor application

Specifications

Dimensions (HxWxD)	58,7x151,4mm
Series	eneo SN-Series
Camera Type	Fisheye Kamera
Resolution Standard	8 Megapixel
System	True Day&Night
Sensor size	1/1,7"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	4000x3000
Image Transmission Rate	30 fps

ISD-59P0010P0A

Continuation of the specifications

Day&Night switch	ICR
Sensitivity	0,3 Lux at F2,8
Digital Noise Reduction	yes
Lens Type	fixed focal length
Focal Length	1,29 mm
Iris Control	DC
Digital Zoom	yes
Observe (62 px/m)	25 m
Recognize (125 px/m)	11 m
Identify (250 px/m)	5 m
Detect (25px/m)	60 m
Horizontal Angle of View	360°
MOD (Minimum Object Distance)	0,1 m
Illumination	Infrared
Color (housing)	white
Housing material	Metal
Heater	no
Blower	no
Alarm inputs	1
Alarm outputs	1
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSD card, microSDXC card
Analysis functions	Defog, Intrusion, Loitering detection, Motion analysis, Motion detection, Person recognition, Tampering protection, Trip wire plus object counting
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	12.5W @ PoE, 15W @ VDC12V
Power over Ethernet	IEEE 802.3af
Vandal proof	yes
Operating temperature	-20°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Certifications	IK10
Protection rating	IP66
Low Speed Shutter	yes
Backlight Compensation	BLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Camera type	Dome
Audio	2 Way Audio

ISD-59P0010P0A

Continuation of the specifications

Remote configuration	Browser
Illumination range	approx. 10m
Weight	750g
Manufacturer order number	220196

Optional Accessory

SKU	Name	Description
225730	AK-9B	Camera junction box for DH-6, Dome-WB4
218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug

Optional Services

SKU	Name	Description
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
211124	LACKIERUNG PTZ oder Panoramakamera	Extra charge for special paint PTZ dome or panoramic camera in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

