

# IPP-72A0023MIA

SKU: 220201



1/2,8" Network Dome, PTZ, Day&Night, 23x, H.265, WDR, 1920x1080, Infrared, IP66

## Main Features

1/2.8" Sony STARVIS CMOS-Sensor

Full HD 1920x1080 Pixel, 25/30fps

23x AF Zoom, 5~117mm

Quad Stream H.265, H.264, MJPEG (Smart Codec)

Real time WDR (Wide Dynamic Range) 25/30fps

Intelligent self learning video analysis

Digital Noise Reduction (2DNR/3DNR)

Audio support including audio alarm

Infrared illumination up to 60m

Alarm in- and outputs, micro SD-card

Power supply 12VDC or HPoE

Support ONVIF Profile S und Profile T

## Specifications

Dimensions (HxWxD)	208,3x182,4mm
Series	eneo SN-Series
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps
Day&Night switch	ICR

# IPP-72A0023MIA

Continuation of the specifications

Sensitivity	0,35 Lux at F1,6, 50 IRE
Digital Noise Reduction	yes
Lens Type	auto focus zoom
Focal Length	5 - 117 mm
Iris Control	DC
Zoom Factor	23x
Digital Zoom	yes
Observe (62 px/m)	27 - 590 m
Recognize (125 px/m)	14 - 290 m
Identify (250 px/m)	7 - 140 m
Detect (25px/m)	71 - 1400 m
Horizontal Angle of View	56,6 - 3°
Vertical Angle of View	31,8 - 1,6°
MOD (Minimum Object Distance)	3 m
Illumination	Infrared
Housing	Outdoor
Color (housing)	black, white
Housing material	Aluminium
Heater	no
Blower	yes
Rotation range	360°
Speed (manual)	380°/Sek.
Speed (preset)	380°/Sek.
Video outputs	no
Alarm inputs	4
Alarm outputs	1
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	Cross Counting (CC), Defog, Digital image stabilization, Human (PD), Loitering detection, Motion detection, Perimeter Intrusion Detection (PID), Tampering Detection (TD)
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	22W
Power over Ethernet	IEEE 802.3at
Vandal proof	no
Operating temperature	-20°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Protection rating	IP66

# IPP-72A0023MIA

Continuation of the specifications

Low Speed Shutter	yes
Backlight Compensation	BLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Camera type	PTZ
Audio	2 Way Audio
Remote configuration	Browser
Illumination range	approx. 60m
Weight	2.8kg
Manufacturer order number	220201

## Optional Accessory

SKU	Name	Description
216209	DOME-WB2-W	Wall bracket for IED-63xx Metal series and IEP-63Mxx, MEP-62Mxx
221234	EDMC/CWB-1-W	Wall or Pendant Mount Kit white, for Dome Camera Series MPP-72xx, IPP-72xx
218218	eneo Site Manager	Management Software for eneo IP products

## Optional Services

SKU	Name	Description
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
211124	LACKIERUNG PTZ oder Panoramakamera	Extra charge for special paint PTZ dome or panoramic camera in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

# IPP-72A0023MIA

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

