




IPP-88A0030MIA

SKU: 220203



1/1,7" Network Dome, PTZ, Day&Night, 30x, H.265, WDR, 3840x2160, Infrared, IP66

Main Features

- 1/1,7" Sony STARVIS CMOS-Sensor
- 8.0MP 3840x2160 Pixel, 25/30fps
- 30x AF Zoom, 6~180mm
- Quad Stream H.265, H.264, MJPEG (Smart Codec)
- Real time WDR (Wide Dynamic Range) 25/30fps
- Intelligent self learning video analysis

- Digital Noise Reduction (2DNR/3DNR)
- Audio support including audio alarm
- Infrared illumination up to 200m
- Alarm in- and outputs, micro SD-card
- Power supply 12VDC or UPoE (High-PoE Midspan included)
- Support ONVIF Profile S und Profile T

Specifications

Dimensions (HxWxD)	317,8x201.8mm
Series	eneo SN-Series
Resolution Standard	8 Megapixel
System	True Day&Night
Sensor size	1/1,7"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	3840x2160
Image Transmission Rate	30 fps
Day&Night switch	ICR

IPP-88A0030MIA

Continuation of the specifications

Sensitivity	0,75 Lux at F1,6, 50 IRE
Digital Noise Reduction	yes
Lens Type	auto focus zoom
Focal Length	6 - 180 mm
Iris Control	DC
Zoom Factor	30x
Digital Zoom	yes
Observe (62 px/m)	58 - 1300 m
Recognize (125 px/m)	29 - 640 m
Identify (250 px/m)	14 - 300 m
Detect (25px/m)	140 - 3000 m
Horizontal Angle of View	55,4 - 2,7°
Vertical Angle of View	31,1 - 1,5°
MOD (Minimum Object Distance)	1 m
Illumination	Infrared
Housing	Outdoor
Color (housing)	black, white
Housing material	Aluminium
Heater	no
Blower	yes
Rotation range	360°
Speed (manual)	380°/Sek.
Speed (preset)	380°/Sek.
Video outputs	no
Alarm inputs	4
Alarm outputs	1
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	Cross Counting (CC), Defog, Digital image stabilization, Human (PD), Loitering detection, Motion detection, Perimeter Intrusion Detection (PID), Tampering Detection (TD)
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	28W
Power over Ethernet	HiPoE+
Vandal proof	no
Operating temperature	-30°C ~ +55°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Protection rating	IP66

IPP-88A0030MIA

Continuation of the specifications

Low Speed Shutter	yes
Backlight Compensation	BLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Camera type	PTZ
Audio	2 Way Audio
Remote configuration	Browser
Illumination range	approx. 200m
Weight	5.1kg
Manufacturer order number	220203

Optional Accessory

SKU	Name	Description
220314	EDC-WMB1-W	Wall Mount for PTZ Dome Cameras, white, with Mounting Kit
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
211124	LACKIERUNG PTZ oder Panoramakamera	Extra charge for special paint PTZ dome or panoramic camera in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

