



# IAM-5SE1004MUC

SKU: 220212



Gigabit Switch, Unmanaged, 4x PoE, 2x RJ45 and 2x SFP, 1000Mbps, Industrial Design

## Main Features

- Gigabit PoE switch, DIN Rail
- Gigabit Uplink ports 2xRJ45, 2xSFP
- 4x 10/100/1000 PoE Ports,IEEE 802.3af/at

- Surge protection IEC61000-4-5 (6KV)
- Status LED: Uplink, PoE, Optical port, Power
- Temperature range -40° C ~ +75° C

## Specifications

Dimensions (HxWxD)	46x110x163mm
Type	Unmanaged
Series	eneo Switch
Mounting	DIN rail, wall mount
Blower	no
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
VLAN	no
Ports	2x 10/100/1000Base-TX, 2x 10/100/1000T SFP, 4x 10/100/1000Base-T
PoE ports (number)	4
Management	no
Model	DIN rail module
Supply voltage	48~57 VDC
Power over Ethernet	IEEE 802.3af, IEEE 802.3at

# IAM-5SE1004MUC

Continuation of the specifications

PoE budget	120 W
Operating temperature	-40°C ~ +75°C
Weight	530g
Manufacturer order number	220212

## Optional Accessory

SKU	Name	Description
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

