

IPD-78M3611M5A

SKU: 220930



1/2,5" Network Dome, Fix, 3840x2160, Day&Night, DOL-WDR 3,6-11mm, Infrared, IP67

Main Features

1/2.5" Sony STARVIS CMOS sensor
Resolution max. 3840x2160, 8 Megapixel
Motorised varifocal lens 3,6~11mm
DOL-WDR (120dB) by triple scan images at 30/25fps
VCA video analysis, ONVIF event mapping
Browser independent (IE, Edge, Safari, Firefox, Chrome)

Smart Codec H.265 ROI (Region of interest)
Quad Smart Streaming: H.265(+), H.264(+), MJPEG
Slot for Micro SD Card, HTML5 replay, Audio, Alarm
Power supply PoE, 12VDC or 24VAC
For outdoor use IP66, vandal proofed IK10
Supports ONVIF Profile S and Profile T

Specifications

| | |
|-------------------------|--|
| Dimensions (HxWxD) | 119x140mm |
| Series | eneo Callisto, eneo LN-Series |
| Resolution Standard | 8 Megapixel |
| System | True Day&Night |
| Sensor size | 1/2.5" |
| Imager | CMOS |
| Video compression | H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG |
| Image resolution max. | 3840x2160 |
| Image Transmission Rate | 30 fps |
| Day&Night switch | ICR |

IPD-78M3611M5A

Continuation of the specifications

| | |
|-------------------------------|---|
| Sensitivity | 0,2 Lux at F1,5, 40 IRE |
| Digital Noise Reduction | yes |
| Lens Type | Varifocal (motorized) |
| Focal Length | 3,6 - 11 mm |
| Iris Control | DC |
| Zoom Factor | 3x |
| Digital Zoom | yes |
| Observe (62 px/m) | 40,4 - 119 m |
| Recognize (125 px/m) | 20,2 - 59,2 m |
| Identify (250 px/m) | 9,8 - 28,8 m |
| Detect (25px/m) | 104 - 295 m |
| Horizontal Angle of View | 84 - 40° |
| Vertical Angle of View | 46 - 21° |
| MOD (Minimum Object Distance) | 0,5 m |
| Illumination | Infrared |
| Housing | Indoor, Outdoor |
| Color (housing) | Pantone Cool Gray 1C |
| Color (bubble) | clear |
| Housing material | Aluminium |
| Heater | no |
| Blower | yes |
| Rotation range | +/-173° |
| Video outputs | no |
| Alarm inputs | 1 |
| Alarm outputs | 1 |
| Audio support | yes |
| Ethernet interface | 100Base-TX, 10Base-T |
| Serial interfaces | Ethernet |
| Internal storage | microSDHC card, microSDXC card |
| Analysis functions | Defog, Field detection, Line detection, Motion detection, Object left,removed |
| Mounting | Ceiling mount, Wall mount |
| Supply voltage | 12VDC, 24VAC, PoE |
| Power consumption | 10,8W |
| Power over Ethernet | IEEE 802.3af |
| Vandal proof | yes |
| Operating temperature | -50°C ~ +50°C |
| ONVIF | ONVIF Profile S, ONVIF Profile T |
| Certifications | IK10 |
| Protection rating | IP67 |
| Low Speed Shutter | yes |
| Backlight Compensation | BLC, HLC |

IPD-78M3611M5A

Continuation of the specifications

| | |
|---------------------------|-------------|
| Wide Dynamic Range (WDR) | D-WDR |
| Motion Detector | yes |
| Camera type | Dome |
| Audio | 2 Way Audio |
| Remote configuration | Browser |
| Illumination range | approx. 40m |
| Weight | 1 kg |
| Manufacturer order number | 220930 |

Optional Accessory

| SKU | Name | Description |
|--------|-----------------------|---|
| 209832 | AK-5 | Camera Junction Box, for Callisto Dome series, IP66 |
| 216923 | DOME-S1 | Sun Shield for eneo Callisto Dome Series |
| 209880 | DOME-WB1+DOME/ Basis1 | Wall Bracket & Surface mount base, Callisto Dome line |
| 215644 | DOME-WB3 | Wall bracket for eneo Dome Cameras MED-62xxxxxM0A and IED-62xxxxxM0A |
| 209831 | DOME/BASIS1 | Surface mount base , Callisto Dome line |
| 207192 | DOME/WEDGE2 | Wedge Adapter, Callisto Dome Line |
| 218218 | eneo Site Manager | Management Software for eneo IP products |
| 216472 | IAD-5SG1008MUA | Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop |
| 221334 | IAM-4MU1001M0A | EPOC Signal Converter, BNC to 2-wire cable transmission for EPOC Cameras, Transceiver |

Optional Services

| SKU | Name | Description |
|--------|----------------------------|--|
| 211125 | LACKIERUNG Fix-Dome-Kamera | Extra charge for special paint fixed dome in RAL color |
| 214441 | LACKIERUNG Grundkosten | Painting basic costs once per RAL color and delivery lot |
| 229234 | Vorkonfiguration IP-Kamera | Preconfiguration 1x IP camera Function test, FW update |

IPD-78M3611M5A

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

