



# IED-62M2812MCA

SKU: 220931



1/2,8" Network Dome, Fix, 1920x1080,Day&Night, WDR, 2,8-12mm, EPOC, IR, IP66

## Main Features

1/2,8" Sony STARVIS CMOS

Resolution max. 1920x1080, 25fps frame rate

Motorised vary focal lens 2,8~12mm with P-Iris

EPOC Ethernet and Power over Coax transmission

Wide Dynamic Range, T-WDR (120dB)

Intelligent self learning video analysis (IntelliVision Technology) Support ONVIF Profile S and Profile T

Quad Streaming: H.264, H.265 x3, MJPEG x1, Smart Codec

Micro SD Card (SDHC, SDXC)

1 x Alarm in and output as well as audio support

Infrared illumination up to 30m

Easy installation, IP66, PoE IEEE 802.3af

## Specifications

Observe (62 px/m)	16 - 55 m
Recognize (125 px/m)	8 - 26 m
Identify (250 px/m)	4 - 13 m
Detect (25px/m)	40 - 130 m
Manufacturer order number	220931

## Optional Accessory

SKU	Name	Description
225730	AK-9B	Camera junction box for DH-6, Dome-WB4

# IED-62M2812MCA

Continuation of accessory

218218	eneo Site Manager	Management Software for eneo IP products
221334	IAM-4MU1001M0A	EPOC Signal Converter, BNC to 2-wire cable transmission for EPOC Cameras, Transceiver
223980	IED-FMH1	Ceiling mount adapter with white cover for fix dome cameras, SN-series

## Optional Services

SKU	Name	Description
211125	LACKIERUNG Fix-Dome-Kamera	Extra charge for special paint fixed dome in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

