

IAM-6MC1001MRA

SKU: 221577



Ethernet Coax Receiver Data & Power over Coax 1 x RJ-45, 1 x BNC

Main Features

EPOC Ethernet and Power over Coax Transmission

RJ45 Ethernet and BNC-Female plug

Max. Transmission Rate 95Mbps Full Duplex

Data Transmission up to 2.4Km

PoC Transmission up to 1.2Km

Power Supply Receiver PoE or 12-57V DC

PoE/PoE+ Power Supply for Transmitter

128 Bit AES Network Encryption

Supports Multi Connection (Daisy Chain, Star)

Surge Protection

Temperature Range (Operating) -20° C bis +60°C

Easy Installation (Plug & Play)

Specifications

Dimensions (HxWxD)	24x61,6x82,4mm
Series	eneo EPOC
Housing	Metal
Color	anthracite
Ethernet interface	100Base-TX, 10Base-T
Data transfer rate max.	95 Mbps
Model	module
Supply voltage	56VDC
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Operating temperature	-20°C ~ +60°C

IAM-6MC1001MRA

Continuation of the specifications

Weight	77g
Manufacturer order number	221577

Optional Accessory

SKU	Name	Description
221334	IAM-4MU1001M0A	EPOC Signal Converter, BNC to 2-wire cable transmission for EPOC Cameras, Transceiver
221276	NE-141/220VAC-57VDC	Power supply input 100-240VAC, output 57VDC 1,2A, for EPOC Transceiver, Transmitter, Rec.

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

