



# IAM-5SE1004MUP

SKU: 221889



Gigabit Switch, Unmanaged 60W, 4x PoE, Industrial Design -40°C~+75°C, PD port

## Main Features

Gigabit PoE Switch, DIN Rail

4x 10/100/1000 PoE Ports, IEEE 802.3ab/af/at/u

1 x SFP Gigabit uplink port

1 x RJ45 Gigabit uplink port, PD-capable (60W PoE input)

PoE watchdog (reboot automatically)

Surge protection IEC61000-4-5 (6KV)

Temperature range -40° C ~ +75° C

Temperature range -40° C ~ +75° C

## Specifications

|                    |  |
|--------------------|--|
| Dimensions (HxWxD) | 46x110x163mm   |
| Type               | Unmanaged  |
| Series             | eneo Switch  |
| Mounting           | DIN rail   |
| Blower             | no   |
| Ethernet interface | 1000Base-T, 100Base-TX, 10Base-T                                       |
| VLAN               | yes  |
| Ports              | 1x 10/100/1000Base-T (PoE-PD), 1x 1000Base-X SFP, 4x 10/100/1000Base-T |
| PoE ports (number) | 4  |
| Management         | no   |
| Model              | DIN rail module  |
| Supply voltage     | 48~57 VDC, PoE   |

# IAM-5SE1004MUP

Continuation of the specifications

|                           |                            |
|---------------------------|----------------------------|
| Power consumption         | 60W                        |
| Power over Ethernet       | IEEE 802.3af, IEEE 802.3at |
| PoE budget                | 60 W                       |
| Operating temperature     | -40°C ~ +75°C              |
| Weight                    | 540g                       |
| Manufacturer order number | 221889                     |

## Optional Accessory

| SKU    | Name        | Description  |
|--------|-------------|--|
| 216568 | NE-60PoE    | PoE Injector, 60W, for Switch IAD-5SG1004MUA and IAM-5SE1004MUP                |
| 216479 | SFP-0850M10 | SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C     |
| 218758 | SFP-0850M40 | SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C |
| 216478 | SFP-1310M40 | SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C  |
| 216566 | SFP-1310S10 | SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C   |
| 216477 | SFP-1310S40 | SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C  |

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

