



IAR-7SM1024MMB

SKU: 221890



Gigabit Switch, Managed, 24xGb SFP slots, 8xGb RJ45 ports, 4x10Gb uplink SFP slots

Main Features

- Managed L3 switch
- 24x Gigabit SFP slots, 8 shared RJ45 ports
- 4x SFP Gigabit uplink ports
- Fast ring redundancy, reconfiguration <20ms
- Provision of a web-based layer 3 network management
- Support high speed data forwarding

- Very suitable for forwarding large amounts of video data in sec
- ESD protection IEC61000-4-5 standard
- Supports two high performance power supplies for redundant o
- Fast installation and commissioning
- Temperature range -10 ° C ~ + 50 ° C
- Suitable for wall / rack mounting and desktop use

Specifications

Manufacturer order number	221890
---------------------------	--------

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218759	SFP-0850M10-10G	SFP Modul, 10Gbps, 300m, Multimode, 850nm, Duplex LC Connector, -5°~+70°C

IAR-7SM1024MMB

Continuation of accessory

218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
218760	SFP-1310S10-10G	SFP Modul, 10Gbps, 10km, Singlemode, 1310nm, Duplex LC Connector, -5°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

