

IPP-62A0020M0B

SKU: 222184



1/2,8" Network Dome, PTZ, Day&Night, 20x, H.265, WDR, 1920x1080, PoE, IP66

Main Features

1/2.8" Sony STARVIS CMOS-Sensor

Full HD 1920x1080 Pixel, 25/30fps

23x AF Zoom, 4.7~94mm

Quad Stream H.265, H.264, MJPEG (Smart Codec)

Real time WDR (Wide Dynamic Range) 25/30fps

Intelligent motion detector

Digital Noise Reduction (2DNR/3DNR)

Audio support including audio alarm

Alarm in- and outputs, micro SD-card slot

Power supply 12VDC, 24VAC or PoE

IK10 IK shock resistance degree

Support ONVIF Profile S und Profile T

Specifications

Dimensions (HxWxD)	150x154mm
Series	eneo SN-Series
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps
Day&Night switch	ICR

IPP-62A0020M0B

Continuation of the specifications

Sensitivity	0,2 Lux at F1,6, 50 IRE
Digital Noise Reduction	yes
Lens Type	auto focus zoom
Focal Length	4,7 - 94 mm
Iris Control	DC
Zoom Factor	20x
Digital Zoom	16x
Observe (62 px/m)	28 - 550 m
Recognize (125 px/m)	13 - 270 m
Identify (250 px/m)	7 - 130 m
Detect (25px/m)	70 - 1370 m
Horizontal Angle of View	55,5 - 3°
Vertical Angle of View	32,4 - 1,7°
MOD (Minimum Object Distance)	1 m
Illumination	no
Housing	Indoor, Outdoor
Color (housing)	white
Color (bubble)	clear
Housing material	Aluminium
Heater	optional
Window heater	optional
Blower	yes
Rotation range	360°
Speed (manual)	380°/Sek.
Speed (preset)	380°/Sek.
Video outputs	no
Alarm inputs	4
Alarm outputs	1
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	Defog, Digital image stabilization, Motion detection, Perimeter Intrusion Detection (PID), Tampering Detection (TD)
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, 24VAC, PoE
Power consumption	12W
Power over Ethernet	IEEE 802.3af
Vandal proof	yes
Operating temperature	-20°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T

IPP-62A0020M0B

Continuation of the specifications

Certifications	IK10
Protection rating	IP66
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Camera type	PTZ
Audio	2 Way Audio
Remote configuration	Browser
Weight	1.6 kg
Manufacturer order number	222184

Optional Accessory

SKU	Name	Description
216209	DOME-WB2-W	Wall bracket for IED-63xx Metal series and IEP-63Mxx, MEP-62Mxx
221234	EDMC/CWB-1-W	Wall or Pendant Mount Kit white, for Dome Camera Series MPP-72xx, IPP-72xx
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
211124	LACKIERUNG PTZ oder Panoramakamera	Extra charge for special paint PTZ dome or panoramic camera in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

IPP-62A0020M0B

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

