

# AES-5SF0036M1A

SKU: 223916



1/3" Mini Dome, Fix, clear, 3,6mm, 960TVL, 12VDC, vandalism protect

## Main Features

1/3" Fix dome camera with Sony CCD

Integrated lens F2.0/3.6mm

Resolution of 960 horizontal lines

Automatic shutter control

Digital signal processing (DSP)

Automatic white balance (ATW)

White-coloured aluminium die-cast casing

Clear Lexan bubble, 57mm

Easy indoor installation

For wall or ceiling mounting

Vandal resistant

## Specifications

Dimensions (HxWxD)	60,5x80
Series	eneo COAXIZE
Horizontal resolution	960 TVL
System	electronic Day&Night
Sensor size	1/3"
Imager	CCD
Day&Night switch	Electronic
Sensitivity	0,1 Lux at F1,2, 50 IRE
Digital Noise Reduction	yes
Lens Type	fixed focal length

# AES-5SF0036M1A

Continuation of the specifications

Focal Length	3,6 mm
Digital Zoom	no
Observe (62 px/m)	12,6 m
Recognize (125 px/m)	5,9 m
Identify (250 px/m)	2,8 m
Detect (25px/m)	32,2 m
Horizontal Angle of View	68°
MOD (Minimum Object Distance)	0,1 m
Illumination	no
Housing	Outdoor
Color (housing)	white
Color (bubble)	clear
Housing material	Aluminium
Heater	no
Video outputs	Composite (CVBS)
Alarm inputs	nein
Alarm outputs	no
Serial interfaces	no
Mounting	Ceiling mount
Supply voltage	12VDC
Power consumption	1.2W
Vandal proof	yes
Operating temperature	-10°C ~ +50°C
Certifications	IK10
Protection rating	IP66
Low Speed Shutter	no
Backlight Compensation	BLC
Wide Dynamic Range (WDR)	no
Motion Detector	no
Camera type	Dome
Weight	260g
Manufacturer order number	223916

## Optional Accessory

SKU	Name	Description
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
236125	MAM-5MM2203M0A	Converter, 4K HD-TVI, HD-CVI, AHD, auf HDMI, Indoor 12VDC
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug

# AES-5SF0036M1A

Continuation of accessory

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

