



MEB-65M2713M0A

SKU: 225246



1/2.7" HD Camera, Day&Night, 2592x1944, Infrared, 2,7-13mm, 12VDC, IP66

Main Features

1/2,7" CMOS Image Sensor

Resolution max. 2592x1920

Multisignal: HD-TVI, AHD, CVI, CVBS

Motorised varifocal 2.7~13mm

Removable infrared cut filter

2D/-3D-DNR noise reduction

Digital Wide Dynamic Range (D-WDR), Defog

LDC function(Lens Distortion Correction)

OSD menu control and signal switching possible via joystick in

Compact housing for outdoor IP66

Specifications

Serial interfaces protocols	UTC (HD-Signal Format)
Observe (62 px/m)	22 - 68 m
Recognize (125 px/m)	10 - 34 m
Identify (250 px/m)	3 - 16 m
Detect (25px/m)	55 - 170 m
Manufacturer order number	225246

Optional Accessory

SKU	Name	Description
225730	AK-9B	Camera junction box for DH-6, Dome-WB4

MEB-65M2713M0A

Continuation of accessory

225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive

Optional Services

SKU	Name	Description
211123	LACKIERUNG Bulletkamera	Extra charge for special paint bullet camera in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229233	Vorkonfiguration analoge Kamera	Preconfiguration 1x analog camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

