



MPP-62A0020M0B

SKU: 226625

EAN: 4260229840351



1/2,8" HD Analogue Dome, PTZ, Day&Night, 20x, 4,7-94mm, 1920x1080, WDR, IP66

Abb. ähnlich

Main Features

1/2,8" Sony STARVIS CMOS-Sensor

20x Auto Focus Zoom, 4.7 ~ 94mm / 16x Digital

Resolution max. 1920x1080 (Full HD)

Separate outputs for HD signals and composite

Signal formats: HD-TVI, AHD selectable, composite

Real time WDR (Wide Dynamic Range) 25 / 30fps

Compact design for in- and outdoor applications

3D DNR noise reduction, auto-calibration

Protected areas, Defog function

Alarm inputs and outputs, 12VDC/24VAC, IK10, IP66

Specifications

EAN/GTIN	4260229840351
Dimensions (HxWxD)	150x154mm
Serial interfaces protocols	Fastrax Fastrax IIE Pelco D Pelco P UTC (HD-Signal Format)
Series	eneo COAXIZE
Resolution Pixels	1280x720, 1920x1080, 720x576
Resolution Pixels	1280x720, 1920x1080, 720x576
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Day&Night switch	ICR

MPP-62A0020M0B

Continuation of the specifications

Sensitivity	0,35 Lux at F1,6, 50 IRE
Digital Noise Reduction	yes
Lens Type	auto focus zoom
Focal Length	4,7 - 94 mm
Zoom Factor	20x
Digital Zoom	16x
Observe (62 px/m)	28 - 550 m
Recognize (125 px/m)	13 - 270 m
Identify (250 px/m)	7 - 130 m
Detect (25px/m)	70 - 1370 m
Horizontal Angle of View	55,5 - 3°
Vertical Angle of View	32,4 - 1,7°
MOD (Minimum Object Distance)	1 m
Illumination	no
Housing	Indoor, Outdoor
Color (housing)	white
Color (bubble)	clear
Housing material	Aluminium
Window heater	optional
Blower	yes
Rotation range	360°
Speed (manual)	380°/Sek.
Speed (preset)	380°/Sek.
Video outputs	AHD, Composite (CVBS), HD-TVI
Alarm inputs	4
Alarm outputs	2
Serial interfaces	Coaxitron (HD Protocol), RS-485
Analysis functions	Defog, DIS (digital image stabilisation)
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, 24VAC
Power consumption	12W
Vandal proof	yes
Operating temperature	-20°C ~ +50°C
Certifications	IK10
Protection rating	IP66
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Signal format	AHD @ 2MP, Composite (FBAS), HD-TVI @ 2MP
Camera type	PTZ

MPP-62A0020M0B

Continuation of the specifications

Frame rate	25/30fps @ 1920x1080p, 50/60fps @ 1280x720p
Aperture range (F)	F1.6~F3.0
Weight	1.6 kg
Manufacturer order number	226625

Optional Accessory

SKU	Name	Description
216209	DOME-WB2-W	Wall bracket for IED-63xx Metal series and IEP-63Mxx, MEP-62Mxx
221234	EDMC/CWB-1-W	Wall or Pendant Mount Kit white, for Dome Camera Series MPP-72xx, IPP-72xx
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
236125	MAM-5MM2203M0A	Converter, 4K HD-TVI, HD-CVI, AHD, auf HDMI, Indoor 12VDC
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive

Optional Services

SKU	Name	Description
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
211124	LACKIERUNG PTZ oder Panoramakamera	Extra charge for special paint PTZ dome or panoramic camera in RAL color
229233	Vorkonfiguration analoge Kamera	Preconfiguration 1x analog camera Function test, FW update

MPP-62A0020M0B

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

