



# MPP-62A0020M0B

SKU: 226625

EAN: 4260229840351



1/2,8" HD Analogue Dome, PTZ, Day&Night, 20x, 4,7-94mm, 1920x1080, WDR, IP66

Abb. ähnlich

## Main Features

1/2,8" Sony STARVIS CMOS-Sensor

20x Auto Focus Zoom, 4.7 ~ 94mm / 16x Digital

Resolution max. 1920x1080 (Full HD)

Separate outputs for HD signals and composite

Signal formats: HD-TVI, AHD selectable, composite

Real time WDR (Wide Dynamic Range) 25 / 30fps

Compact design for in- and outdoor applications

3D DNR noise reduction, auto-calibration

Protected areas, Defog function

Alarm inputs and outputs, 12VDC/24VAC, IK10, IP66

## Specifications

|                             |  |
|-----------------------------|--|
| EAN/GTIN                    | 4260229840351  |
| Dimensions (HxWxD)          | 150x154mm  |
| Serial interfaces protocols | Fastrax Fastrax IIE Pelco D Pelco P UTC (HD-Signal Format) |
| Series                      | eneo COAXIZE   |
| Resolution Pixels           | 1280x720, 1920x1080, 720x576                               |
| Resolution Pixels           | 1280x720, 1920x1080, 720x576                               |
| System                      | True Day&Night   |
| Sensor size                 | 1/2.8"   |
| Imager                      | CMOS   |
| Day&Night switch            | ICR  |

# MPP-62A0020M0B

Continuation of the specifications

|                               |   |
|-------------------------------|---|
| Sensitivity                   | 0,35 Lux at F1,6, 50 IRE                  |
| Digital Noise Reduction       | yes                                       |
| Lens Type                     | auto focus zoom                           |
| Focal Length                  | 4,7 - 94 mm                               |
| Zoom Factor                   | 20x                                       |
| Digital Zoom                  | 16x                                       |
| Observe (62 px/m)             | 28 - 550 m                                |
| Recognize (125 px/m)          | 13 - 270 m                                |
| Identify (250 px/m)           | 7 - 130 m                                 |
| Detect (25px/m)               | 70 - 1370 m                               |
| Horizontal Angle of View      | 55,5 - 3°                                 |
| Vertical Angle of View        | 32,4 - 1,7°                               |
| MOD (Minimum Object Distance) | 1 m                                       |
| Illumination                  | no  |
| Housing                       | Indoor, Outdoor                           |
| Color (housing)               | white                                     |
| Color (bubble)                | clear                                     |
| Housing material              | Aluminium                                 |
| Window heater                 | optional                                  |
| Blower                        | yes                                       |
| Rotation range                | 360°                                      |
| Speed (manual)                | 380°/Sek.                                 |
| Speed (preset)                | 380°/Sek.                                 |
| Video outputs                 | AHD, Composite (CVBS), HD-TVI             |
| Alarm inputs                  | 4   |
| Alarm outputs                 | 2   |
| Serial interfaces             | Coaxitron (HD Protocol), RS-485           |
| Analysis functions            | Defog, DIS (digital image stabilisation)  |
| Mounting                      | Ceiling mount, Wall mount                 |
| Supply voltage                | 12VDC, 24VAC                              |
| Power consumption             | 12W                                       |
| Vandal proof                  | yes                                       |
| Operating temperature         | -20°C ~ +50°C                             |
| Certifications                | IK10                                      |
| Protection rating             | IP66                                      |
| Low Speed Shutter             | yes                                       |
| Backlight Compensation        | BLC, HLC                                  |
| Wide Dynamic Range (WDR)      | WDR 120dB                                 |
| Motion Detector               | yes                                       |
| Signal format                 | AHD @ 2MP, Composite (FBAS), HD-TVI @ 2MP |
| Camera type                   | PTZ                                       |

# MPP-62A0020M0B

Continuation of the specifications

|                           |   |
|---------------------------|---|
| Frame rate                | 25/30fps @ 1920x1080p, 50/60fps @ 1280x720p |
| Aperture range (F)        | F1.6~F3.0                                   |
| Weight                    | 1.6 kg                                      |
| Manufacturer order number | 226625                                      |

## Optional Accessory

| SKU    | Name           | Description  |
|--------|----------------|--|
| 216209 | DOME-WB2-W     | Wall bracket for IED-63xx Metal series and IEP-63Mxx, MEP-62Mxx                      |
| 221234 | EDMC/CWB-1-W   | Wall or Pendant Mount Kit white, for Dome Camera Series MPP-72xx, IPP-72xx           |
| 225085 | MAM-5DC1004M0A | Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output                      |
| 220299 | MAM-5MM1001M0A | Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor            |
| 236125 | MAM-5MM2203M0A | Converter, 4K HD-TVI, HD-CVI, AHD, auf HDMI, Indoor 12VDC                            |
| 212984 | TVA-1201TRA    | UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V |
| 212985 | TVA-1201TRP    | UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive     |

## Optional Services

| SKU    | Name                               | Description  |
|--------|------------------------------------|--|
| 214441 | LACKIERUNG Grundkosten             | Painting basic costs once per RAL color and delivery lot                 |
| 211124 | LACKIERUNG PTZ oder Panoramakamera | Extra charge for special paint PTZ dome or panoramic camera in RAL color |
| 229233 | Vorkonfiguration analoge Kamera    | Preconfiguration 1x analog camera Function test, FW update               |

# MPP-62A0020M0B

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

