



IAR-7SG1016MMB

SKU: 226691



Gigabit Switch, Managed 270W, 16x PoE, 4x SFP, 10/100/1000 Mbps, 19", 1 U

Main Features

PoE Switch, Rack Montage

Gigabit Uplink Ports: 4x SFP

16x 10/100/1000 PoE Ports, IEEE 802.3af/at

Up to 30W per port, total $\leq 270W$

Fast Ring-Redundant, Reconfiguration <20ms

ESD protection IEC61000-4-5 standard

Managed L2 switch

Web configuration, Web management

VLAN, PoE management, MAC address table

Port mirroring, password

Temperature range -10° C ~ +50° C

Rack mounting brackets included

Specifications

Dimensions (HxWxD)	44,5x442x320mm
Type	Layer2 switch
Series	eneo Switch
Mounting	19" rack
Blower	yes
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
VLAN	yes
Ports	16x 10/100/1000Base-T, 4x 1000Mbps SFP, Console RJ45-RS232, OOB 10/100Base-TX
PoE ports (number)	16
Management	yes

IAR-7SG1016MMB

Continuation of the specifications

Model	Rack Mount
Supply voltage	100~240VAC
Power consumption	320W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
PoE budget	270 W
Operating temperature	-10°C ~ +50°C
Weight	4.5Kg
Manufacturer order number	226691

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

