

# ISD-52F0023WSA

SKU: 227007



1/2,8" Network Dome, WDR, 1920x1080, Day&Night, 2,3mm H.265, PoE, 12VDC, Surface

Abb. ähnlich

## Main Features

1 / 2.8 "2.0 MP Sony STARVIS CMOS sensor

Resolution max. 1920x1080 (Full HD)

Fixed focal length 2.3mm, day / night lens (HFOV 135 °!)

Quad Streaming (H.265, H.264, MJPEG)

Intelligent self-learning video analysis (IntelliVision inside)

WDR 120dB, Smart BLC

Slot for micro SD memory card

ONVIF compliance, PoE IEEE802.af, 12VDC

Audio, alarm inputs and outputs

Privacy zones, password protection, browser-independent

Increasing the refresh rate when moving

Suitable for indoor and outdoor use IP66

## Specifications

Dimensions (HxWxD)	91,5x120mm
Series	eneo SN-Series
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps
Day&Night switch	ICR

# ISD-52F0023WSA

Continuation of the specifications

Sensitivity	0,08 Lux at F2,2, 40 IRE
Digital Noise Reduction	yes
Lens Type	fixed focal length
Focal Length	2,3 mm
Iris Control	no
Digital Zoom	yes
Observe (62 px/m)	14 m 13,4 m
Recognize (125 px/m)	8 m 6,6 m
Identify (250 px/m)	4 m 3,4 m
Detect (25px/m)	35 m 33,2 m
Horizontal Angle of View	135°
Vertical Angle of View	75°
MOD (Minimum Object Distance)	0,3 m
Illumination	no
Housing	Outdoor
Color (housing)	white
Color (bubble)	clear
Housing material	Aluminium
Heater	no
Blower	no
Alarm inputs	1
Alarm outputs	1
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Internal storage	microSDHC card, microSDXC card
Analysis functions	Defog, DIS (digital image stabilisation), Motion detection, Perimeter Intrusion Detection (PID), Tampering Detection (TD)
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	4.8W
Power over Ethernet	IEEE 802.3af
Vandal proof	yes
Operating temperature	-20°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Certifications	IK10
Protection rating	IP66
Low Speed Shutter	yes
Backlight Compensation	BLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Camera type	Dome

# ISD-52F0023WSA

Continuation of the specifications

Audio	2 Way Audio
Remote configuration	Browser
Weight	880g
Manufacturer order number	227007

## Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products

## Optional Services

SKU	Name	Description
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

