



ISM-78F0021W0A

SKU: 227047



1/2.8" Network Module Camera, 3840x2160, Day&Night, WDR, 2.1mm, H.265, PoE, 12VDC

Main Features

-
- 1/2.8" Sony STARVIS CMOS Sensor
-
- Excellent light sensitivity
-
- Resolution max. 3840x2160 (4K)
-
- Lens fixed focal length 2.1mm
-
- DOL-WDR (120dB) by triple scan images at 30/25fps
-
- Motion Detection, Privacy Zones, Slow Shutter
-

-
- Browser independent (IE, Edge, Safari, Firefox, Chrome)
-
- Smart Codec H.265 ROI (Region of Interest)
-
- Supports ONVIF Profile S and Profile T
-
- Operating temperature -20°C ~ +50°C
-
- Dimensions 50x50x64mm
-
- Power supply PoE or 12VDC
-

Specifications

| | |
|-------------------------|--|
| Dimensions (HxWxD) | 63x50x50mm |
| Series | eneo AN-Series |
| Camera Type | Board Camera |
| Resolution Standard | 8 Megapixel |
| System | True Day&Night |
| Sensor size | 1/2.8" |
| Imager | CMOS |
| Video compression | H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream) |
| Image resolution max. | 3840x2160 |
| Image Transmission Rate | 30 fps |

ISM-78F0021W0A

Continuation of the specifications

| | |
|-------------------------------|--|
| Day&Night switch | ICR |
| Sensitivity | 0,03 Lux at F2,0, 40 IRE |
| Digital Noise Reduction | yes |
| Lens Type | fixed focal length |
| Focal Length | 2,1 mm |
| Digital Zoom | yes |
| Observe (62 px/m) | 28,5 m |
| Recognize (125 px/m) | 13,3 m |
| Identify (250 px/m) | 5,2 m |
| Detect (25px/m) | 74,2 m |
| Horizontal Angle of View | 109° |
| Vertical Angle of View | 58° |
| MOD (Minimum Object Distance) | 0,5 m |
| Illumination | no |
| Housing | without housing |
| Heater | no |
| Blower | yes |
| Alarm inputs | nein |
| Alarm outputs | no |
| Audio support | no |
| Ethernet interface | 100Base-TX, 10Base-T |
| Serial interfaces | Ethernet |
| Internal storage | no |
| Analysis functions | Motion detection, Tampering Detection (TD) |
| Mounting | Einbaumodul |
| Supply voltage | 12VDC, PoE |
| Power consumption | 7W |
| Power over Ethernet | IEEE 802.3af |
| Operating temperature | -20°C ~ +50°C |
| ONVIF | ONVIF Profile S, ONVIF Profile T |
| Low Speed Shutter | yes |
| Backlight Compensation | BLC, HLC |
| Wide Dynamic Range (WDR) | D-WDR |
| Motion Detector | yes |
| Camera type | Platine |
| Remote configuration | Browser |
| Weight | 112g |
| Manufacturer order number | 227047 |

Optional Accessory

| SKU | Name | Description |
|-----|------|-------------|
|-----|------|-------------|

ISM-78F0021W0A

Continuation of accessory

| | | |
|--------|-------------------|--|
| 218218 | eneo Site Manager | Management Software for eneo IP products |
| 216472 | IAD-5SG1008MUA | Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop |

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

