



ISM-78F0021W0A

SKU: 227047



1/2.8" Network Module Camera, 3840x2160, Day&Night, WDR, 2.1mm, H.265, PoE, 12VDC

Main Features

-
- 1/2.8" Sony STARVIS CMOS Sensor
-
- Excellent light sensitivity
-
- Resolution max. 3840x2160 (4K)
-
- Lens fixed focal length 2.1mm
-
- DOL-WDR (120dB) by triple scan images at 30/25fps
-
- Motion Detection, Privacy Zones, Slow Shutter
-

-
- Browser independent (IE, Edge, Safari, Firefox, Chrome)
-
- Smart Codec H.265 ROI (Region of Interest)
-
- Supports ONVIF Profile S and Profile T
-
- Operating temperature -20°C ~ +50°C
-
- Dimensions 50x50x64mm
-
- Power supply PoE or 12VDC
-

Specifications

Dimensions (HxWxD)	63x50x50mm
Series	eneo AN-Series
Camera Type	Board Camera
Resolution Standard	8 Megapixel
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream)
Image resolution max.	3840x2160
Image Transmission Rate	30 fps

ISM-78F0021W0A

Continuation of the specifications

Day&Night switch	ICR
Sensitivity	0,03 Lux at F2,0, 40 IRE
Digital Noise Reduction	yes
Lens Type	fixed focal length
Focal Length	2,1 mm
Digital Zoom	yes
Observe (62 px/m)	28,5 m
Recognize (125 px/m)	13,3 m
Identify (250 px/m)	5,2 m
Detect (25px/m)	74,2 m
Horizontal Angle of View	109°
Vertical Angle of View	58°
MOD (Minimum Object Distance)	0,5 m
Illumination	no
Housing	without housing
Heater	no
Blower	yes
Alarm inputs	nein
Alarm outputs	no
Audio support	no
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	no
Analysis functions	Motion detection, Tampering Detection (TD)
Mounting	Einbaumodul
Supply voltage	12VDC, PoE
Power consumption	7W
Power over Ethernet	IEEE 802.3af
Operating temperature	-20°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR
Motion Detector	yes
Camera type	Platine
Remote configuration	Browser
Weight	112g
Manufacturer order number	227047

Optional Accessory

SKU	Name	Description
-----	------	-------------

ISM-78F0021W0A

Continuation of accessory

218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

