

IPD-68M3611P5A

SKU: 227050



1/2,5" Network Dome, Fix, 3840x2160, Day&Night, DOL-WDR, 3,6-11mm, Infrared, Indoor

Main Features

- 1/2.5" Sony STARVIS CMOS sensor
- Resolution max. 3840x2160, 8 Megapixel
- Motorised varifocal lens 3.6~11mm
- DOL-WDR (120dB) by triple scan images at 30/25fps
- VCA video analysis, ONVIF event mapping
- Browser independent (IE, Edge, Safari, Firefox, Chrome)

- Smart Codec H.265 ROI (Region of interest)
- Quad Smart Streaming: H.265(+), H.264(+), MJPEG
- Slot for Micro SD Card, HTML5 replay
- Power supply PoE or 12VDC
- Wedge adapter included (10° inclination)
- Supports ONVIF Profile S and Profile T

Specifications

Dimensions (HxWxD)	94x116mm
Series	eneo Callisto Indoor, eneo LN-Series
Resolution Standard	8 Megapixel
System	True Day&Night
Sensor size	1/2.5"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	3840x2160
Image Transmission Rate	30 fps
Day&Night switch	ICR

IPD-68M3611P5A

Continuation of the specifications

Sensitivity	0,2 Lux at F1,5, 40 IRE
Digital Noise Reduction	yes
Lens Type	Varifocal (motorized)
Focal Length	3,6 - 11 mm
Iris Control	DC
Zoom Factor	3x
Digital Zoom	yes
Observe (62 px/m)	40,4 - 119 m
Recognize (125 px/m)	20,2 - 59,2 m
Identify (250 px/m)	9,8 - 28,8 m
Detect (25px/m)	104 - 295 m
Horizontal Angle of View	84 - 40°
Vertical Angle of View	46 - 21°
MOD (Minimum Object Distance)	0,5 m
Illumination	Infrared
Housing	Indoor
Color (housing)	white
Color (bubble)	clear
Housing material	Plastic
Heater	no
Blower	yes
Rotation range	+/-165°
Video outputs	no
Alarm inputs	nein
Alarm outputs	no
Audio support	no
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	Defog, Field detection, Line detection, Motion detection, Object left,removed
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	8,5W
Power over Ethernet	IEEE 802.3af
Vandal proof	yes
Operating temperature	-10°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR
Motion Detector	yes

IPD-68M3611P5A

Continuation of the specifications

Camera type	Dome
Remote configuration	Browser
Illumination range	approx. 30m
Weight	300g
Manufacturer order number	227050

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description
211125	LACKIERUNG Fix-Dome-Kamera	Extra charge for special paint fixed dome in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

