



ICB-65M2713M5A

SKU: 227051



1/2,8" Network Camera, 2592x1944, Day&Night, DOL-WDR, 2,7-13,5mm, Infrared, IP67

Main Features

- 1/2.8" Sony STARVIS CMOS sensor
- Resolution max. 2592x1944, 5 Megapixel
- Motorised varifocal lens 2,7~13.5mm
- DOL-WDR (120dB) by triple scan images at 30/25fps
- VCA video content analysis, ONVIF event mapping
- Browser independent (IE, Edge, Safari, Firefox, Chrome)

- Smart Codec H.265 ROI (Region of interest) HTML5 playback
- Quad Smart Streaming: H.265(+), H.264(+), MJPEG
- Micro SD Card, HTML5 replay, Audio, Alarm
- Power supply PoE IEEE 802.3af
- Integrated connection box including connection board
- Supports ONVIF Profile S and Profile T

Specifications

Observe (62 px/m)	32,5 - 105,4 m
Recognize (125 px/m)	15,3 - 52 m
Identify (250 px/m)	6,4 - 25,7 m
Detect (25px/m)	84 - 262,7 m
Manufacturer order number	227051

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products

ICB-65M2713M5A

Continuation of accessory

216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop
202641	PM-42A	Pole mount adaptor for eneo Candid, Candid S, Candid M, WB1, AK-5, AK-4

Optional Services

SKU	Name	Description
211123	LACKIERUNG Bulletkamera	Extra charge for special paint bullet camera in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

