

# IPD-75M2713M5A

SKU: 227052



1/2,8" Network Dome, Fix, 2592x1944, Day&Night, DOL-WDR, 2,7-13,5mm, Infrared, IP67

Abb. ähnlich

## Main Features

1/2.8" Sony STARVIS CMOS sensor  
Resolution max. 2592x1944, 5 Megapixel  
Motorised varifocal lens 2,7~13.5mm  
DOL-WDR (120dB) by triple scan images at 30/25fps  
VCA (Video Content Analysis), ONVIF event mapping  
Browser independent (IE, Edge, Safari, Firefox, Chrome)

Smart Codec H.265 ROI (Region of interest)  
Quad Smart Streaming: H.265(+), H.264(+), MJPEG  
Micro SD Card, HTML5 replay, Audio, Alarm  
Power supply PoE, 12VDC or 24VAC  
For outdoor use IP67, vandal proofed IK10  
Supports ONVIF Profile S and Profile T

## Specifications

|                         |                                                                    |
|-------------------------|--------------------------------------------------------------------|
| Dimensions (HxWxD)      | 119x140mm                                                          |
| Series                  | eneo Callisto, eneo LN-Series                                      |
| Resolution Standard     | 5 Megapixel                                                        |
| System                  | True Day&Night                                                     |
| Sensor size             | 1/2.8"                                                             |
| Imager                  | CMOS                                                               |
| Video compression       | H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG |
| Image resolution max.   | 2592x1944                                                          |
| Image Transmission Rate | 30 fps                                                             |
| Day&Night switch        | ICR                                                                |

# IPD-75M2713M5A

Continuation of the specifications

|                               |                                                                                |
|-------------------------------|--------------------------------------------------------------------------------|
| Sensitivity                   | 0,05 Lux at F1,6, 40 IRE                                                       |
| Digital Noise Reduction       | yes                                                                            |
| Lens Type                     | Varifocal (motorized)                                                          |
| Focal Length                  | 2,7 - 13,5 mm                                                                  |
| Iris Control                  | DC                                                                             |
| Zoom Factor                   | 4x                                                                             |
| Digital Zoom                  | yes                                                                            |
| Observe (62 px/m)             | 32,5 - 105,4 m                                                                 |
| Recognize (125 px/m)          | 15,3 - 52 m                                                                    |
| Identify (250 px/m)           | 6,4 - 25,7 m                                                                   |
| Detect (25px/m)               | 84 - 262,7 m                                                                   |
| Horizontal Angle of View      | 97 - 29°                                                                       |
| Vertical Angle of View        | 54 - 17°                                                                       |
| MOD (Minimum Object Distance) | 0,5 m                                                                          |
| Illumination                  | Infrared                                                                       |
| Housing                       | Indoor, Outdoor                                                                |
| Color (housing)               | Pantone Cool Gray 1C                                                           |
| Color (bubble)                | clear                                                                          |
| Housing material              | Aluminium                                                                      |
| Heater                        | no                                                                             |
| Blower                        | yes                                                                            |
| Rotation range                | +/-173°                                                                        |
| Video outputs                 | no                                                                             |
| Alarm inputs                  | 1                                                                              |
| Alarm outputs                 | 1                                                                              |
| Audio support                 | yes                                                                            |
| Ethernet interface            | 100Base-TX, 10Base-T                                                           |
| Serial interfaces             | Ethernet                                                                       |
| Internal storage              | microSDHC card, microSDXC card                                                 |
| Analysis functions            | Defog, Field detection, Line detection, Motion detection, Object left, removed |
| Mounting                      | Ceiling mount, Wall mount                                                      |
| Supply voltage                | 12VDC, 24VAC, PoE                                                              |
| Power consumption             | 10,8W                                                                          |
| Power over Ethernet           | IEEE 802.3af                                                                   |
| Vandal proof                  | yes                                                                            |
| Operating temperature         | -50°C ~ +50°C                                                                  |
| ONVIF                         | ONVIF Profile S, ONVIF Profile T                                               |
| Certifications                | IK10                                                                           |
| Protection rating             | IP67                                                                           |
| Low Speed Shutter             | yes                                                                            |
| Backlight Compensation        | BLC, HLC                                                                       |

# IPD-75M2713M5A

Continuation of the specifications

|                           |             |
|---------------------------|-------------|
| Wide Dynamic Range (WDR)  | D-WDR       |
| Motion Detector           | yes         |
| Camera type               | Dome        |
| Audio                     | 2 Way Audio |
| Remote configuration      | Browser     |
| Illumination range        | approx. 40m |
| Weight                    | 1 kg        |
| Manufacturer order number | 227052      |

## Optional Accessory

| SKU    | Name                  | Description                                                                           |
|--------|-----------------------|---------------------------------------------------------------------------------------|
| 209832 | AK-5                  | Camera Junction Box, for Callisto Dome series, IP66                                   |
| 216923 | DOME-S1               | Sun Shield for eneo Callisto Dome Series                                              |
| 209880 | DOME-WB1+DOME/ Basis1 | Wall Bracket & Surface mount base, Callisto Dome line                                 |
| 215644 | DOME-WB3              | Wall bracket for eneo Dome Cameras MED-62xxxxxM0A and IED-62xxxxxM0A                  |
| 209831 | DOME/BASIS1           | Surface mount base , Callisto Dome line                                               |
| 207192 | DOME/WEDGE2           | Wedge Adapter, Callisto Dome Line                                                     |
| 218218 | eneo Site Manager     | Management Software for eneo IP products                                              |
| 221334 | IAM-4MU1001M0A        | EPOC Signal Converter, BNC to 2-wire cable transmission for EPOC Cameras, Transceiver |

## Optional Services

| SKU    | Name                       | Description                                              |
|--------|----------------------------|----------------------------------------------------------|
| 211125 | LACKIERUNG Fix-Dome-Kamera | Extra charge for special paint fixed dome in RAL color   |
| 214441 | LACKIERUNG Grundkosten     | Painting basic costs once per RAL color and delivery lot |
| 229234 | Vorkonfiguration IP-Kamera | Preconfiguration 1x IP camera Function test, FW update   |

# IPD-75M2713M5A

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

