

IPD-75M2713M5A

SKU: 227052



Abb. ähnlich

1/2,8" Network Dome, Fix, 2592x1944, Day&Night, DOL-WDR, 2,7-13,5mm, Infrared, IP67

Main Features

1/2.8" Sony STARVIS CMOS sensor
Resolution max. 2592x1944, 5 Megapixel
Motorised varifocal lens 2,7~13.5mm
DOL-WDR (120dB) by triple scan images at 30/25fps
VCA (Video Content Analysis), ONVIF event mapping
Browser independent (IE, Edge, Safari, Firefox, Chrome)

Smart Codec H.265 ROI (Region of interest)
Quad Smart Streaming: H.265(+), H.264(+), MJPEG
Micro SD Card, HTML5 replay, Audio, Alarm
Power supply PoE, 12VDC or 24VAC
For outdoor use IP67, vandal proofed IK10
Supports ONVIF Profile S and Profile T

Specifications

Dimensions (HxWxD)	119x140mm
Series	eneo Callisto, eneo LN-Series
Resolution Standard	5 Megapixel
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	2592x1944
Image Transmission Rate	30 fps
Day&Night switch	ICR

IPD-75M2713M5A

Continuation of the specifications

Sensitivity	0,05 Lux at F1,6, 40 IRE
Digital Noise Reduction	yes
Lens Type	Varifocal (motorized)
Focal Length	2,7 - 13,5 mm
Iris Control	DC
Zoom Factor	4x
Digital Zoom	yes
Observe (62 px/m)	32,5 - 105,4 m
Recognize (125 px/m)	15,3 - 52 m
Identify (250 px/m)	6,4 - 25,7 m
Detect (25px/m)	84 - 262,7 m
Horizontal Angle of View	97 - 29°
Vertical Angle of View	54 - 17°
MOD (Minimum Object Distance)	0,5 m
Illumination	Infrared
Housing	Indoor, Outdoor
Color (housing)	Pantone Cool Gray 1C
Color (bubble)	clear
Housing material	Aluminium
Heater	no
Blower	yes
Rotation range	+/-173°
Video outputs	no
Alarm inputs	1
Alarm outputs	1
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	Defog, Field detection, Line detection, Motion detection, Object left,removed
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, 24VAC, PoE
Power consumption	10,8W
Power over Ethernet	IEEE 802.3af
Vandal proof	yes
Operating temperature	-50°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Certifications	IK10
Protection rating	IP67
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC

IPD-75M2713M5A

Continuation of the specifications

Wide Dynamic Range (WDR)	D-WDR
Motion Detector	yes
Camera type	Dome
Audio	2 Way Audio
Remote configuration	Browser
Illumination range	approx. 40m
Weight	1 kg
Manufacturer order number	227052

Optional Accessory

SKU	Name	Description
209832	AK-5	Camera Junction Box, for Callisto Dome series, IP66
216923	DOME-S1	Sun Shield for eneo Callisto Dome Series
209880	DOME-WB1+DOME/ Basis1	Wall Bracket & Surface mount base, Callisto Dome line
215644	DOME-WB3	Wall bracket for eneo Dome Cameras MED-62xxxxxM0A and IED-62xxxxxM0A
209831	DOME/BASIS1	Surface mount base , Callisto Dome line
207192	DOME/WEDGE2	Wedge Adapter, Callisto Dome Line
218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop
221334	IAM-4MU1001M0A	EPOC Signal Converter, BNC to 2-wire cable transmission for EPOC Cameras, Transceiver

Optional Services

SKU	Name	Description
211125	LACKIERUNG Fix-Dome-Kamera	Extra charge for special paint fixed dome in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

IPD-75M2713M5A

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

