

# IPD-65M2713P5A

SKU: 227053



1/2,8" Network Dome, Fix, 2592x1944, Day&Night, DOL-WDR, 2,7-13,5mm, Infrared, Indoor

## Main Features

1/2.8" Sony STARVIS CMOS sensor  
Resolution max. 2592x1944, 5 Megapixel  
Motorised varifocal lens 2,7~13.5mm  
DOL-WDR (120dB) by triple scan images at 30/25fps  
VCA (Video Content Analysis), ONVIF event mapping  
Browser independent (IE, Edge, Safari, Firefox, Chrome)

Smart Codec H.265 ROI (Region of interest)  
Quad Smart Streaming: H.265(+), H.264(+), MJPEG  
Micro SD Card, HTML5 replay  
Power supply PoE or 12VDC  
Wedge adapter included (10° inclination)  
Supports ONVIF Profile S and Profile T

## Specifications

|                         |  |
|-------------------------|--|
| Dimensions (HxWxD)      | 94x116mm   |
| Series                  | eneo Callisto Indoor, eneo LN-Series                               |
| Resolution Standard     | 5 Megapixel  |
| System                  | True Day&Night   |
| Sensor size             | 1/2.8"   |
| Imager                  | CMOS   |
| Video compression       | H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG |
| Image resolution max.   | 2592x1944  |
| Image Transmission Rate | 30 fps   |
| Day&Night switch        | ICR  |

# IPD-65M2713P5A

Continuation of the specifications

|                               |   |
|-------------------------------|---|
| Sensitivity                   | 0,05 Lux at F1,6, 40 IRE  |
| Digital Noise Reduction       | yes   |
| Lens Type                     | Varifocal (motorized)   |
| Focal Length                  | 2,7 - 13,5 mm   |
| Iris Control                  | DC  |
| Zoom Factor                   | 4x  |
| Digital Zoom                  | yes   |
| Observe (62 px/m)             | 32,5 - 105,4 m  |
| Recognize (125 px/m)          | 15,3 - 52 m   |
| Identify (250 px/m)           | 6,4 - 25,7 m  |
| Detect (25px/m)               | 84 - 262,7 m  |
| Horizontal Angle of View      | 97 - 29°  |
| Vertical Angle of View        | 54 - 17°  |
| MOD (Minimum Object Distance) | 0,5 m   |
| Illumination                  | Infrared  |
| Housing                       | Indoor  |
| Color (housing)               | white   |
| Color (bubble)                | clear   |
| Housing material              | Plastic   |
| Heater                        | no  |
| Blower                        | yes   |
| Rotation range                | +/-165°   |
| Video outputs                 | no  |
| Alarm inputs                  | nein  |
| Alarm outputs                 | no  |
| Audio support                 | no  |
| Ethernet interface            | 100Base-TX, 10Base-T  |
| Serial interfaces             | Ethernet  |
| Internal storage              | microSDHC card, microSDXC card  |
| Analysis functions            | Defog, Field detection, Line detection, Motion detection, Object left,removed |
| Mounting                      | Ceiling mount, Wall mount   |
| Supply voltage                | 12VDC, PoE  |
| Power consumption             | 8,5W  |
| Power over Ethernet           | IEEE 802.3af  |
| Vandal proof                  | yes   |
| Operating temperature         | -10°C ~ +50°C   |
| ONVIF                         | ONVIF Profile S, ONVIF Profile T  |
| Low Speed Shutter             | yes   |
| Backlight Compensation        | BLC, HLC  |
| Wide Dynamic Range (WDR)      | D-WDR   |
| Motion Detector               | yes   |

# IPD-65M2713P5A

Continuation of the specifications

|                           |             |
|---------------------------|-------------|
| Camera type               | Dome        |
| Remote configuration      | Browser     |
| Illumination range        | approx. 30m |
| Weight                    | 300g        |
| Manufacturer order number | 227053      |

## Optional Accessory

| SKU    | Name              | Description                              |
|--------|-------------------|--|
| 218218 | eneo Site Manager | Management Software for eneo IP products |

## Optional Services

| SKU    | Name                       | Description  |
|--------|----------------------------|--|
| 211125 | LACKIERUNG Fix-Dome-Kamera | Extra charge for special paint fixed dome in RAL color   |
| 214441 | LACKIERUNG Grundkosten     | Painting basic costs once per RAL color and delivery lot |
| 229234 | Vorkonfiguration IP-Kamera | Preconfiguration 1x IP camera Function test, FW update   |

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

