

ICB-62M2712M5A

SKU: 227054



1/2.8" Network Camera, 1920x1080, Day&Night, DOL-WDR 2,7-12mm, Infrared, IP67

Abb. ähnlich

Main Features

1/2.8" Sony STARVIS CMOS sensor	Smart Codec H.265 ROI (Region of interest)
Resolution max. 1920x1080 (Full HD)	Triple Streaming: H.265(+), H.264(+), MJPEG
Motorised varifocal lens 2,7~12mm	Micro SD Card, HTML5 replay, Audio, Alarm
DOL-WDR (120dB) by triple scan images at 30/25fps	Power supply PoE IEEE 802.3af
Motion Detection, Privacy Zones, Defog	Supports ONVIF Profile S and Profile T
Browser independent (IE, Edge, Safari, Firefox, Chrome)	Integrated connection box including connection board

Specifications

Observe (62 px/m)	17,1 - 55,3 m
Recognize (125 px/m)	8,5 - 27,6 m
Identify (250 px/m)	4,2 - 13,8 m
Detect (25px/m)	42,6 - 137,2 m
Manufacturer order number	227054

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products

ICB-62M2712M5A

Continuation of accessory

216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop
202641	PM-42A	Pole mount adaptor for eneo Candid, Candid S, Candid M, WB1, AK-5, AK-4

Optional Services

SKU	Name	Description
211123	LACKIERUNG Bulletkamera	Extra charge for special paint bullet camera in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

