



IPD-72M2712M5A

SKU: 227055



1/2,8" Network Dome, Fixed, 1920x1080, Day&Night, DOL-WDR, 2,7-12mm, Infrared, IP67

Main Features

- 1/2.8" Sony STARVIS CMOS sensor
- Resolution max. 1920x1080 (Full HD)
- Motorised varifocal lens 2,7~12mm
- DOL-WDR (120dB) by triple scan images at 30/25fps
- Motion Detection, Privacy Zones, Defog
- Browser independent (IE, Edge, Safari, Firefox, Chrome)

- Smart Codec H.265 ROI (Region of interest)
- Triple Smart Streaming: H.265(+), H.264(+), MJPEG
- Micro SD Card, HTML5 replay, Audio, Alarm
- Power supply PoE, 12VDC or 24VAC
- For outdoor use IP67, vandal proofed IK10
- Supports ONVIF Profile S and Profile T

Specifications

Observe (62 px/m)	17,1 - 55,3 m
Recognize (125 px/m)	8,5 - 27,6 m
Identify (250 px/m)	4,2 - 13,8 m
Detect (25px/m)	42,6 - 137,2 m
Manufacturer order number	227055

Optional Accessory

SKU	Name	Description
209832	AK-5	Camera Junction Box, for Callisto Dome series, IP66

IPD-72M2712M5A

Continuation of accessory

216923	DOMES-S1	Sun Shield for eneo Callisto Dome Series
209880	DOMES-WB1+DOMES/ Basis1	Wall Bracket & Surface mount base, Callisto Dome line
209831	DOMES/BASIS1	Surface mount base , Callisto Dome line
207192	DOMES/WEDGE2	Wedge Adapter, Callisto Dome Line
218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop
221334	IAM-4MU1001M0A	EPOC Signal Converter, BNC to 2-wire cable transmission for EPOC Cameras, Transceiver

Optional Services

SKU	Name	Description
211125	LACKIERUNG Fix-Dome-Kamera	Extra charge for special paint fixed dome in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

