



IPD-62M2712P5A

SKU: 227056



1/2,8" Network Dome, Fix, 1920x1080, Day&Night, DOL-WDR, 2,7-12mm, Infrared, Indoor

Main Features

- 1/2.8" Sony STARVIS CMOS sensor
- Resolution max. 1920x1080 (Full HD)
- Motorised varifocal lens 2,7~12mm
- DOL-WDR (120dB) by triple scan images at 30/25fps
- Motion Detection, Privacy Zones, Defog
- Browser independent (IE, Edge, Safari, Firefox, Chrome)

- Smart Codec H.265 ROI (Region of interest)
- Triple Smart Streaming: H.265(+), H.264(+), MJPEG
- Micro SD Card, HTML5 replay
- Power supply PoE or 12VDC
- Wedge adapter included (10° inclination)
- Supports ONVIF Profile S and Profile T

Specifications

Observe (62 px/m)	17,1 - 55,3 m
Recognize (125 px/m)	8,5 - 27,6 m
Identify (250 px/m)	4,2 - 13,8 m
Detect (25px/m)	42,6 - 137,2 m
Manufacturer order number	227056

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products

IPD-62M2712P5A

Continuation of accessory

216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop
--------	----------------	--

Optional Services

SKU	Name	Description
211125	LACKIERUNG Fix-Dome-Kamera	Extra charge for special paint fixed dome in RAL color
214441	LACKIERUNG Grundkosten	Painting basic costs once per RAL color and delivery lot
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

