

IAM-5SE1008MUB

SKU: 228223



Gigabit Switch, 8xPoE 100Mbps, 1x RJ45, 1x SFP 1000Mbps, Unmanaged, Industrial Design

Main Features

Gigabit PoE switch, DIN Rail

Gigabit Uplink ports 1xRJ45, 1xSFP

8x 10/100 PoE Ports, IEEE 802.3af/at

Up to 30W per port

Surge protection IEC61000-4-5 (6KV)

Status LED: Uplink, PoE, Optical port, Power

PoE reset button for each port

CCTV mode allows transmission up to 250m @ 10Mbps

Temperature range -40° C ~ +75° C

Specifications

Dimensions (HxWxD)	46,5x163x110,5mm
Type	Unmanaged
Series	eneo Switch
Mounting	DIN rail, wall mount
Blower	no
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
VLAN	yes
Ports	1x 10/100/1000Base-Tx, 1x 10/100/1000T SFP, 8x 10/100Base-TX
PoE ports (number)	8
Management	no
Model	DIN rail module

IAM-5SE1008MUB

Continuation of the specifications

Supply voltage	48~57 VDC
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
PoE budget	120 W
Operating temperature	-40°C ~ +75°C
Weight	530g
Manufacturer order number	228223

Optional Accessory

SKU	Name	Description
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

