



# IAM-5SE1008IUA

SKU: 230034



Switch unmanaged, 120W, 8xPoE 1xRJ45 ,1xSFP  
Gigabit Industrial Design

## Main Features

Ethernet PoE Switch, DIN Rail

Gigabit Uplink ports 1xRJ45, 1xSFP

8x 10/100 PoE Ports,IEEE 802.3af/at

Up to 30W per port, Total  $\leq$ 240W (optional power supply)

Surge protection IEC61000-4-5 (6KV)

Status LED: Uplink, PoE, Optical port, Power

CCTV mode allows transmission up to 250m @ 10Mbps

Temperature range -30° C ~ +65° C

## Specifications

Dimensions (HxWxD)	44x159x110mm
Type	Unmanaged
Series	eneo Switch
Mounting	desktop
Blower	no
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
VLAN	yes
Ports	1x 10/100/1000Base-T, 1x 10/100/1000T SFP, 8x 10/100Base-TX
PoE ports (number)	8
Management	no
Model	housing
Supply voltage	48~57 VDC

# IAM-5SE1008IUA

Continuation of the specifications

Power over Ethernet	IEEE 802.3af, IEEE 802.3at
PoE budget	240 W
Operating temperature	-30°C ~ 65°C
Weight	500g
Manufacturer order number	230034

## Optional Accessory

SKU	Name	Description
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216567	SFP-0850MM10	SFP Modul, 155Mbps, 2km, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

