



IAM-5SE1008IUA

SKU: 230034



Switch unmanaged, 120W, 8xPoE 1xRJ45 ,1xSFP
Gigabit Industrial Design

Main Features

Ethernet PoE Switch, DIN Rail

Gigabit Uplink ports 1xRJ45, 1xSFP

8x 10/100 PoE Ports,IEEE 802.3af/at

Up to 30W per port, Total ≤240W (optional power supply)

Surge protection IEC61000-4-5 (6KV)

Status LED: Uplink, PoE, Optical port, Power

CCTV mode allows transmission up to 250m @ 10Mbps

Temperature range -30° C ~ +65° C

Specifications

| | |
|--------------------|---|
| Dimensions (HxWxD) | 44x159x110mm |
| Type | Unmanaged |
| Series | eneo Switch |
| Mounting | desktop |
| Blower | no |
| Ethernet interface | 1000Base-T, 100Base-TX, 10Base-T |
| VLAN | yes |
| Ports | 1x 10/100/1000Base-T, 1x 10/100/1000T SFP, 8x 10/100Base-TX |
| PoE ports (number) | 8 |
| Management | no |
| Model | housing |
| Supply voltage | 48~57 VDC |

IAM-5SE1008IUA

Continuation of the specifications

| | |
|---------------------------|----------------------------|
| Power over Ethernet | IEEE 802.3af, IEEE 802.3at |
| PoE budget | 240 W |
| Operating temperature | -30°C ~ 65°C |
| Weight | 500g |
| Manufacturer order number | 230034 |

Optional Accessory

| SKU | Name | Description |
|--------|--------------|--|
| 216479 | SFP-0850M10 | SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C |
| 218758 | SFP-0850M40 | SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C |
| 216567 | SFP-0850MM10 | SFP Modul, 155Mbps, 2km, Multimode, 850nm, Duplex LC Connector, 0°~+70°C |
| 216478 | SFP-1310M40 | SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C |
| 216566 | SFP-1310S10 | SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C |
| 216477 | SFP-1310S40 | SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C |

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

