



IAM-6SE1008IMA

SKU: 230035



Gigabit Switch, Managed, 240W, Layer 3, 8xPoE, 4x SFP 10G, Industrial Design

Main Features

| | |
|---|--|
| 8-Port Gigabit Switch Managed L3, Fanless | Web configuration, Web management |
| 4x SFP 10 Gigabit Uplink Ports | VLAN, PoE management, MAC address table |
| PoE Standard IEEE 802.3af/at | Port mirroring, password protection |
| Up to 30W per port, total ≤240W (Power supply not included) | Relay Alarm for power failure, cable link down and PoE link down |
| Fast Ring-Redundant, Reconfiguration <20ms | Temperature range -40° C ~ +75° C |
| ESD protection IEC61000-4-5 standard | DIN-rail, Rack mounting brackets included |

Specifications

| | |
|--------------------|---|
| Dimensions (HxWxD) | 95,6x163x110mm |
| Type | Layer3 Switch |
| Series | eneo Switch |
| Mounting | DIN rail, wall mount |
| Blower | no |
| Ethernet interface | 1000Base-T, 100Base-TX, 10Base-T |
| VLAN | yes |
| Ports | 4x 10Gbit SFP, 8x 10/100/1000Base-T, Console RJ45-RS232 |
| PoE ports (number) | 8 |
| Management | yes |

IAM-6SE1008IMA

Continuation of the specifications

| | |
|---------------------------|----------------------------|
| Model | DIN rail module |
| Supply voltage | 48~57 VDC |
| Power consumption | 260W max. |
| Power over Ethernet | IEEE 802.3af, IEEE 802.3at |
| PoE budget | 240 W |
| Operating temperature | -40°C ~ +75°C |
| Weight | 1.9kg |
| Manufacturer order number | 230035 |

Optional Accessory

| SKU | Name | Description |
|--------|-------------------|--|
| 218218 | eneo Site Manager | Management Software for eneo IP products |
| 216479 | SFP-0850M10 | SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C |
| 218759 | SFP-0850M10-10G | SFP Modul, 10Gbps, 300m, Multimode, 850nm, Duplex LC Connector, -5°~+70°C |
| 218758 | SFP-0850M40 | SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C |
| 216478 | SFP-1310M40 | SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C |
| 216566 | SFP-1310S10 | SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C |
| 218760 | SFP-1310S10-10G | SFP Modul, 10Gbps, 10km, Singlemode, 1310nm, Duplex LC Connector, -5°~+70°C |
| 216477 | SFP-1310S40 | SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C |

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

