



IAR-7SE2024MMA

SKU: 230037



Gigabit Switch, Managed, 250W, Layer 2, 24xPoE, 4x SFP 1G, Wall-/Rack mounting, Desktop

Main Features

24-Port Gigabit PoE L2 Managed Ethernet Switch

4x SFP Gigabit Uplink Ports

PoE Standard IEEE 802.3af/at (PSE)

Up to 30W per port, total $\leq 250W$

Fast Ring-Redundant, Reconfiguration <20ms

Surge Immunity 6kV, Standard: IEC6000-4-5

ESD 6 kV Contact Discharge, 8kV Air Discharge, standard: IEC

Web configuration, Web management

VLAN, PoE management, MAC address table

Port mirroring, password protection

Temperature range $-10^{\circ}C \sim +50^{\circ}C$

Rack mounting brackets included

Specifications

Manufacturer order number	230037
---------------------------	--------

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, $0^{\circ} \sim +70^{\circ}C$
218758	SFP-0850M40	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, $-40^{\circ} \sim +70^{\circ}C$

IAR-7SE2024MMA

Continuation of accessory

216567	SFP-0850MM10	SFP Modul, 155Mbps , 2km, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

